

LED RECESSED DOWNLIGHT



MESALED Downlight LED Isolated Driver

- ❑ Isolator Led Driver
- ❑ High Brightness
- ❑ High Energy Saving
- ❑ Long Life Time up to 25,000hrs



Item Code	Type	Wattage	Voltage	PF	Luminous Flux	CRI	Beam Angle	Dimension (mm)	Cut Hole (mm)	Lifetime (h)	Quantity
MSL-R1212	○ Round	12w	220-240v	0.5	1080lm	80	120°	Ø 145 (4")	Ø135	25,000	40/ctn
MSL-S1212	□ Square	12w	220-240v	0.5	1080lm	80	120°	145 x 145 (4")	135 x 135	25,000	40/ctn
MSL-R1818	○ Round	18w	220-240v	0.5	1620lm	80	120°	Ø 170 (6")	Ø160	25,000	40/ctn
MSL-S1818	□ Square	18w	220-240v	0.5	1620lm	80	120°	170 x 170 (6")	160 x 160	25,000	40/ctn
MSL-R2020	○ Round	20w	220-240v	0.5	1920lm	80	120°	Ø 220 (8")	Ø 210	25,000	40/ctn
MSL-S2020	□ Square	20w	220-240v	0.5	1920lm	80	120°	220 x 220 (8")	210 x 210	25,000	40/ctn

Colour Temperature available:



3 Color 3000k Warm White 4000k Cool White 6500k Daylight