

# LED SURFACE DOWNLIGHT



## MESALED Surface Downlight LED Isolated Driver

- ❑ Isolator Led Driver
- ❑ High Brightness
- ❑ High Energy Saving
- ❑ Long Life Time up to 25,000hrs



Item Code	Type	Wattage	Voltage	PF	Luminous Flux	CRI	Beam Angle	Dimension (mm)	Lifetime (h)	Quantity
MSL-RD0612	○ Round	12w	220-240v	0.5	1050lm	80	120°	Ø 165 (4")	25,000	40/ctn
MSL-SQ0612	□ Square	12w	220-240v	0.5	1050lm	80	120°	165 x 165 (4")	25,000	40/ctn
MSL-RD0818	○ Round	18w	220-240v	0.5	1620lm	80	120°	Ø 170 (6")	25,000	40/ctn
MSL-SQ0818	□ Square	18w	220-240v	0.5	1620lm	80	120°	170 x 170 (6")	25,000	40/ctn
MSL-RD1024	○ Round	24w	220-240v	0.5	1920lm	80	120°	Ø 220 (8")	25,000	40/ctn
MSL-SQ1024	□ Square	24w	220-240v	0.5	1920lm	80	120°	220 x 220 (8")	25,000	40/ctn
MSL-RD1030	○ Round	30w	220-240v	0.5	1920lm	80	120°	220 x 220 (8")	25,000	40/ctn
MSL-SQ1030	□ Square	30w	220-240v	0.5	1920lm	80	120°	220 x 220 (8")	25,000	40/ctn

Colour Temperature available:

