

# LED Surface Downlight

**fonemax**<sup>®</sup>  
Quality . Reliable . Service



Preview



Colour:

Daylight 6000K / Cool White  
4000K / Warm White 3300K



**LowCarbonHomes**  
Improving Energy Efficiency



AC85-265V/50-60Hz



50,000 Hours

Model	Power (W)	Luminous	Color Rendering Index (CRI)	Power Factor	Beam Angle	Shape	Dimension (mm)	Weight (kg)
SUR12WR	12W	1650LM	>80	>0.6	120°	Round	Ø155 x 35	0.66
SUR20WR	20W	2200LM	>80	>0.6	120°	Round	Ø210 x 28	0.70
SUR26WR	26W	2860LM	>80	>0.6	120°	Square	Ø285 x 28	0.74
SUR12WS	12W	1650LM	>80	>0.6	120°	Square	155 x 155 x 35	0.66
SUR20WS	20W	2200LM	>80	>0.6	120°	Square	210 x 210 x 28	0.70
SUR26WS	26W	2860LM	>80	>0.6	120°	Square	285 x 285 x 28	0.74



Application



Bathroom



Bedroom



Classroom



Corridor



Gym



Kitchen



Library



Living Room



Office



Restaurant



School



Shopping Centre



Shop & Boutique



Showroom



Retail