

LED SLIM Downlight



Preview



Preview



Colour:



LowCarbonHomes
Improving Energy Efficiency



Daylight 6000K / Cool White 4000K / Warm White 3300K



AC85-265V/50-60Hz



50,000 Hours

Model	Power (W)	Luminous	Color Rendering Index (CRI)	Power Factor	Beam Angle	Shape	Dimension (mm)	Cut-Out Size (mm)	Weight (kg)
150R	12W	1450LM	>80	>0.6	120°	Round	Ø145 x 5	Ø120	0.42
170R	17W	1650LM	>80	>0.6	120°	Round	Ø170 x 5	Ø160	0.45
225R	20W	1850LM	>80	>0.6	120°	Round	Ø225 x 6	Ø205	0.48
150S	12W	1450LM	>80	>0.6	120°	Square	145 x 145 x 5	120 x 120	0.42
170S	17W	1650LM	>80	>0.6	120°	Square	170 x 170 x 5	160 x 160	0.45
225S	20W	1850LM	>80	>0.6	120°	Square	225 x 225 x 6	205 x 205	0.48



Application



Bathroom



Bedroom



Classroom



Corridor



Gym



Kitchen



Library



Living Room



Office



Restaurant



School



Shopping Centre



Shop & Boutique



Showroom



Retails