

LED Flood Light

fonemax[®]
Quality . Reliable . Service



Colour:

LowCarbonHomes
Improving Energy Efficiency



Daylight 6000K / Cool White 4000K / Warm White 3000K AC220-240V/50-60Hz 25,000 Hours IP65

Model	Power (W)	Luminous	Input Voltage	Color Rendering Index (CRI)	Power Factor	Beam Angle	Dimension (mm)	Weight (kg)
FNM1P-30W	30W	2400LM	AC220-240V	>80	>0.9	120°	145 x 139.5 x 35	0.3
FNM1P-50W	50W	4000LM	AC220-240V	>80	>0.9	120°	196 x 173 x 40.5	0.55
FNM1P-100W	100W	8000LM	AC220-240V	>80	>0.9	120°	269 x 230 x 40	1.06
FNM1P-150W	150W	12,000LM	AC220-240V	>80	>0.9	120°	339.5 x 291.5 x 42	1.55
FNM1P-200W	200W	16,000LM	AC220-240V	>80	>0.9	120°	404 x 331 x 43.5	2.7

More Specification

- **【Materials】** Dia Casting Aluminium
- **【Working Temperature】** 45°C

Feature

- No UV or IR Radiation.
- High-brightness SMD LED.
- High energy efficiency, low power consumption.
- Long life span, low temperature rising, 120° angle.

Application



Billboard



Construction



Exhibition



Facade



Factory



Fair



Garden



Manufacturing Bay



Monument



Port & Dock



Sport Area



Warehouse