

LED FTB-Flood Light Series

fonemax[®]
Quality . Reliable . Service



Preview



Colour:



LowCarbonHomes
Improving Energy Efficiency



Daylight 6000K /
Warm White 3300K



AC85-277V
/50-60Hz



50,000
Hours



IP66

Model	Power (W)	Luminous	Input Voltage	Color Rendering Index (CRI)	Power Factor	Beam Angle	Dimension (mm)	Weight (kg)
FTB-10W	10W	1100LM	AC85-265V	>80	>0.95	120°	122 x 107 x 37	0.4
FTB-30W	30W	3300LM	AC85-265V	>80	>0.95	120°	195 x 165 x 40	0.9
FTB-50W	50W	5500LM	AC85-265V	>80	>0.95	120°	230 x 195 x 57	1.3
FTB-100W	100W	11000LM	AC85-265V	>80	>0.95	120°	297 x 250 x 57	2.3
FTB-150W	150W	16500LM	AC85-265V	>80	>0.95	120°	355 x 290 x 57	3.3
FTB-200W	200W	22000LM	AC85-265V	>80	>0.95	120°	428 x 328 x 65	4.4
FTB-300W	300W	27000LM	AC85-277V	>80	>0.95	120°	500 x 400 x 65	7.2



More Specification

Lighting Effect: 100LM/W

LED Driver: High Quality Isolator Driver

LED Type: 2835 SMD

Working Temperature: Ta= -20°C ~ 40°C



Application

Billboard Construction Exhibition Facade Factory Fair Garden Manufacturing Bay Monument Port & Dock Sport Area Warehouse

