

LED Flood Light Outdoor

fonemax[®]
Quality . Reliable . Service



Preview



Colour:

LowCarbonHomes
Improving Energy Efficiency

RoHS
COMPLIANT

energy saving

1 YEAR WARRANTY

CE



Daylight 6500K / Cool White 4000K /
Warm White 3300K & 3200K



AC200-
265V/50-60Hz



50,000
Hours



IP66

Model	Power (W)	Luminous	Input Voltage	Color Rendering Index (CRI)	Power Factor	Beam Angle	Dimension (mm)	Weight (kg)	Color Temperature
LCSMD30	30W	3000LM	AC200-265V	>80	>0.9	120°	220 x 170 x 35	0.64	6500K, 4000K, 3300K
LCSMD50	50W	5000LM	AC200-265V	>80	>0.9	120°	232 x 210 x 35	0.8	6500K, 4000K, 3300K
LCSMD100	100W	10,000LM	AC200-265V	>80	>0.9	120°	320 x 270 x 40	1.5	6500K, 3200K
LCSMD200	200W	20,000LM	AC200-265V	>80	>0.9	120°	445 x 335 x 50	2.85	6500K, 3200K

More Specification

Lighting Effect:
90LM/W Light Surge: L-
N2KV Bulb Qty: 36 pcs

LED Type: SMD2835
Housing: Dia-Casting
AL

LED Driver: DOB + Lighting Surge
2KV Installed Height: 3-5m

Application

