

LED SMD Flood Light

fonemax[®]
Quality . Reliable . Service



Preview



Colour:



LowCarbonHomes
Improving Energy Efficiency



Daylight 6000K / Cool White
4000K / Warm White 3000K



AC100-
265V/50-60Hz



30,000
Hours



IP65

Model	Power (W)	Luminous	Input Voltage	Color Rendering Index (CRI)	Power Factor	Beam Angle	Dimension (mm)	Weight (kg)
AX-SMD-50W	50W	5000LM	AC100-265V	>70	>0.97	120°	216 x 155 x 44	0.935
AX-SMD-100W	100W	10,000LM	AC100-265V	>70	>0.97	120°	290 x 214 x 47	1.82
AX-SMD-150W	150W	15,000LM	AC100-265V	>70	>0.97	120°	319 x 260 x 55	2.212
AX-SMD-200W	200W	20,000LM	AC100-265V	>70	>0.97	120°	372 x 267 x 55	3.5
AX-SMD-300W	300W	30,000LM	AC100-265V	>70	>0.97	120°	432 x 318 x 55	4.875
AX-SMD-400W	400W	40,000LM	AC100-265V	>70	>0.97	120°	493 x 370 x 55	6.23

More Specification

Lighting Effect: 110LM/W
LED Chips: 60pcs

LED Type: 3030 Chip
Material: Aluminum

Working Temperature:
Ta= -20°C ~ 50°C

Application



Billboard

Construction

Exhibition

Facade

Factory

Fair

Garden

Manufacturing
Bay

Monument

Port & Dock

Sport Area

Warehouse