


LED Panel Light

fonemax[®]
Quality . Reliable . Service



Preview



Colour:



LowCarbonHomes
Improving Energy Efficiency



Daylight 6500K
Cool White 4000K



AC220-
265V/50-60Hz



50,000 Hours



IP 25

| Model | Power (W) | Luminous | Color Rendering Index (CRI) | Power Factor | Beam Angle | Shape | Dimension (mm) | Cut-Out Size (mm) | Weight (kg) |
|-------|-----------|----------|-----------------------------|--------------|------------|--------|----------------|-------------------|-------------|
| FB5 | 50W | 5000LM | >80 | >0.95 | 120° | Square | 600 x 600 | 559 x 559 | 1 |
| FB6 | 100W | 10,000M | >80 | >0.95 | 120° | Square | 600 x 1250 | 559 x 1200 | 3.7 |



More Specification



Operating Temperature: -25°~50°C



Application

Feature

- Ultra-thin integrated flat panel light ultra-thin + spray white
- Low P stroboscopic
- No stroboscopic drive
- Super Book Fashion

Bathroom



Bedroom



Classroom



Corridor



Gym



Kitchen



Library



Living Room



Office



Restaurant



School



Shopping Centre



Shop & Boutique



Showroom



Retails

