

LED Street Light SMD Series

fonemax[®]
Quality . Reliable . Service



Preview



Colour:



LowCarbonHomes
Improving Energy Efficiency



Daylight 5000K / Cool White 4000K /
Warm White 3000K



AC80-
265V/50-60Hz



50,000
Hours



IP65

Model	Power (W)	Luminous	Input Voltage	Color Rendering Index (CRI)	Power Factor	Beam Angle	Dimension (mm)	Weight (kg)
LB50 SMD	50W	5000LM	AC85-265V	>70	>0.97	120°	550 x 200 x 75	1.6
LB100 SMD	100W	10,000LM	AC85-265V	>70	>0.97	120°	702 x 245 x 100	2.3
LB150 SMD	150W	15,000LM	AC85-265V	>70	>0.97	120°	770 x 280 x 100	3



More Specification

Housing Color: Black
Driver: Isolator Driver
LED Type: SMD Chips

Operating Temperature: -40°~60°C
Material: Stainless steel screw + Slim housing

Feature

- Suitable for surface mount.
- Ideal for harsh environment application.
- 100 lumens per watt help to reduce energy saving.
- Ideal for high moisture areas subject to the possibility of abuse.
- Built-in constant current LED driver with efficient LED module.



Application



Street



Road