



SP 1 EYEBALL

Specification

Item code	Product Description	Watt	CCT (K)	Luminous flux (lm)	CRI	Beam angle	Hole size (mm)	Product size (W X H) (mm)
N0424-0400	LED 3W 3000K 36° white crystal bright SP1 ceiling light	3 W	3000K	243	80	36°	Φ 75	Φ 90 X 42
N0424-0401	LED 3W 4000K 36° white crystal bright SP1 ceiling light	3 W	4000K	258	80	36°	Φ 75	Φ 90 X 42
N0424-0402	LED 5W 3000K 36° white crystal bright SP1 ceiling light	5 W	3000K	425	80	36°	Φ 75	Φ 90 X 42
N0424-0403	LED 5W 4000K 36° white crystal bright SP1 ceiling light	5 W	4000K	455	80	36°	Φ 75	Φ 90 X 42

Notes:

- 1) Due to the special conditions of manufacturing processes of LED, the typical data of technical parameters can only reflect statistical figures and do not necessarily correspond to the actual parameters of each single product which could differ from the typical data.
- 2) Exceeding maximum ratings for operation voltage will cause hazardous overload and will likely destroy the LED module.
- 3) Exceeding maximum ratings for operation and storage temperature will reduce expected life time or destroy the LED module.