



LED PAR SERIES

LYKEN[®]



L3-R20



L3-R38



L3-R38

IP65



Model	Power	Efficacy	Test Lumen	Volts	Base	CRI (Ra)	Power Factor	Beam Angle	Drive	Lamp size (mm)	Color Temp.
L3-R20D	12W	100lm/W	1200lm	85-265V	E27/B22	>80	>0.5	180°	IC	Φ97*127	6500K
L3-R20W	12W	100lm/W	1200lm	85-265V	E27/B22	>80	>0.5	180°	IC	Φ97*127	3000K
L3-R38D	15W	100lm/W	1500lm	85-265V	E27/B22	>80	>0.5	180°	IC	Φ125*125	6500K
L3-R38W	15W	100lm/W	1500lm	85-265V	E27/B22	>80	>0.5	180°	IC	Φ125*125	3000K
L3-R38R	15W			85-265V	E27/B22	>80	>0.5	180°	IC	Φ125*125	RED
L3-R38Y	15W			85-265V	E27/B22	>80	>0.5	180°	IC	Φ125*125	YELLOW
L3-R38B	15W			85-265V	E27/B22	>80	>0.5	180°	IC	Φ125*125	BLUE
L3-R38G	15W			85-265V	E27/B22	>80	>0.5	180°	IC	Φ125*125	GREEN