



LED FLOOD LIGHT (PF 0.95)



APPLICATION

- Ideal for Parking Areas, Gardens, Billboard, Facade Lightings, and All Commercial or Residential Areas.




FEATURES

- High Brightness and Long Life LED Chips (15,000Hrs).
- Operating Temperature -20° C ~ 50° C.
- Solid Aluminium Die-Casting and Non-Corrosive Housing.
- Textured Glass Material Diffuser.
- No External Driver Required (DOB) and High Energy Efficiency.



10 KV SURGE PROTECTION
(Starts from 100W/150W/200W)



MODEL	POWER (W)	CCT (K _T)	LUMEN (LM)	SIZE L x W x H (mm)	NET WEIGHT (kg)	PACKING
BSFL-8010	10W	6500	800	89 x 66 x 25	0.1	60/CTN
BSFL-8030	30W	6500	2400	143 x 100 x 23	0.3	30/CTN
BSFL-8050	50W	6500	5000	177.7 x 125 x 30	0.5	20/CTN
BSFL-8100	100W	6500	10000	266 x 190 x 30	1.7	10/CTN
BSFL-8150	150W	6500	15000	321 x 222 x 34	2.8	5/CTN
BSFL-8200	200W	6500	20000	385 x 265 x 34	3.3	5/CTN
BSFL-8300	300W	6500	30000	435 x 318 x 65	4.5	5/CTN

