

PFL6 SERIES

LED Sensor Flood Light



SPECIFICATION	PFL6-2030S PFL6-2065S	PFL6-3030S PFL6-3065S	PFL6-5030S PFL6-5065S	PFL6-10030S PFL6-10065S
Type	Sensor Flood Light	Sensor Flood Light	Sensor Flood Light	Sensor Flood Light
Power	20W	30W	50W	100W
Size (mm)	103*99*27	115*111*29	139*135*29	256*246*31.6
Carton	50 Unit / Carton	30 Unit / Carton	20 Unit / Carton	10 Unit / Carton
LED Chip	SMD 2835, 24 LED	SMD 2835, 36 LED	SMD 2835, 60 LED	SMD 2835, 120 LED
Input Voltage	AC127-265V 50Hz			
Driver	High-Power DOB, Wide Input Voltage Range, Low Profile with Build-In Inductor			
Power Factor	PF0.5			
Surge	2KV			
Cable	PVC 15cm, 3 Cores, 0.75 Square Millimeters, 15cm in Length			
Lumen	90-100LM/W			
Color Temp.	3000K / 6500K			
Sensor IP	IP54			
Beam Angle	120°			
CRI	>80			
IP Rating	IP65/66			
Material	Aluminum Die-Casting + Tempered Glass			
Environmental Temp.	-40°C to +45°C			

