



Modular Mirror Reflector T- Bar Ceiling - Recess Mounted

Goodlite
United U-LI Goodlite Sdn Bhd

General Data

- **Model** : ILB/ AL/ LED
- **Housing** : Heavy gauge die formed & fully welded End caps for superior body rigidity.
- **Surface Finishing** : Epoxy Powder coated & oven baked.
- **Optical Control Unit** : Highly polished anodised aluminium parabolic reflectors in combination with double parabolic cross-vanes. Also available in matt finishing.

Electrical Circuitry

- **Lamp Type** : Linear LED Lamp:G13 Holder
- **Power** :
- **Lamp Lens** :
- **Input Voltage** :
- **Beam Angle** :
- **PF** :
- **Safety** :



Application

- Specially design for use in environment where precise brightness control and exceptional low glare is a necessary requirement.
- For recessed installation in Tee Bar Ceiling.
- Available for both Imperial type ceiling and Metric type ceiling.
- Ideal as main lighting for computer labs, administrative centres, schools' centres with CAD facilities, libraries, hospitals, retail outlets.

MODEL NO	DIMENSIONS (mm)			
	L	L1	W	H
ILB 2212/AL/LED	610	598	298	70
ILB 2222/AL/LED	610	598	603	110
ILB 3222/AL/LED	610	598	603	70
ILB 4222/AL/LED	610	598	603	70
ILB 2414/AL/LED	1220	1208	298	70
ILB 2424/AL/LED	1220	1208	603	110
ILB 3424/AL/LED	1220	1208	603	70
ILB 4424/AL/LED	1220	1208	603	70

Features

- Locking rotary type lampholders – premium quality and safety for life.
- Grommet cable entry to protect cable.
- High wiring standard with all internal wires retained. (Wires do not hang down during installation and colour coded)
- Epoxy powder coated and oven baked- not pre-coated. Gives high reflectance and durable finishing with no sharp edges to rust.
- Posi-bolt latching mechanism for easy installation and removal of reflector.