

LED Linear High Bay~HC30A

Applications:



Widely used in Indoor and outdoor high ceiling application, warehouse, factory, industrial facility, exhibition, stadium etc.

Features

- > Specialized asymmetrical beam angle for aisles in warehosue
- ▶ IP65 waterproof chamber and IK10.
- > Protect well in humid and vandal-proof required environment
- \blacktriangleright Beam angle available: 30x70 $^{\circ}$ / 50x90 $^{\circ}$ / 40x120 $^{\circ}$ / 120 $^{\circ}$ / 90 $^{\circ}$ /Tilt 40 $^{\circ}$
- ➢ High Efficacy : 160LM/W

Model	Voltage	Power	PF	Lumen	ССТ	IP	Lifespan	Optional
EGE-HC30A-100	AC120~240V, 50/60 Hz	100	0.95	16000	5000К 4000К 3000К	65	50000 Hours	Dimming Motion Sensor
EGE-HC30A-150		150		24000				
EGE-HC30A-200		200		32000				





CE RoHS 🔊

LED Linear High Bay~LHB09

Special Designed for warehouse contain IP65/66 to prevent humid environment

Applications:

Widely used in Indoor and outdoor high ceiling application, warehouse, factory, industrial facility, exhibition, stadium etc.

Features

- Specialized asymmetrical optic 40° *140° for aisle, workshop and warehouse.
- > Pendent mounting, pipe mounting for multiple installation.
- IP66 and IK10 rated & low UGR control
- Beam angle available: 60° / 90° / 28x85° / 60x120°
- High Efficacy : 155LM/W

Model	Voltage	Power	PF	Lumen	ССТ	IP	Lifespan	Optional
EGE-LHB09-100	AC 200~240V	100W	0.91	15500	5000K 4000K 3000K	66	50000 Hours	Dimming Motion Sensor
EGE-LHB09-150		150W		23250				
EGE-LHB09-200		200W		31000				
EGE-LHB09-240		240W		37200				
EGE-LHB09-300		300W		46500				
EGE-LHB09-400		400W		62000				
EGE-LHB09-480		480W		74400				