

LED Hi Grow Lamp~ GL01A



Features:

- Durable aluminum with less shading
- High efficiency up to 3.0 $\mu\text{mol}/\text{J}$
- Likeable solution , can connect 4.20 pcs modules
- Full spectrum with IR, high efficiency spectrum R+B
- Double-sided light-emitting design , minimizes light interception and keeps the lower canopy to get the optimal and uniform light.
- Double-sided 120°

Model	Power	PAR Output	ePAR Output	Current Range	Operating Condition	IP	Optional
EGE GL01A-75	75W	176 $\mu\text{mol}/\text{s}$	194 $\mu\text{mol}/\text{s}$	1.5A@50Vdc	0°C to 40°C	65	DC connector
EGE GL01A-150	150W	351 $\mu\text{mol}/\text{s}$	387 $\mu\text{mol}/\text{s}$	3A@50Vdc			



LED Hi Grow Lamp Tube~ GLT02A

Features:

- True wide full spectrum.
- Excellent thermal properties
- External driver, good for reliable and maintainable performance
- Suitable height: 2 to 6 meter.
- Double-sided 120°

Model	Power	PAR Output	ePAR Output	Current Range	Operating Condition	IP	Optional
EGE-GLT02A-40	40W	92 $\mu\text{mol}/\text{s}$	95 $\mu\text{mol}/\text{s}$	0.77A@52Vdc	0°C to 40°C	65	Low/ High Ceiling Mounting Bracket
EGE-GLT02A-75	75W	173 $\mu\text{mol}/\text{s}$	179 $\mu\text{mol}/\text{s}$	1.44A@52Vdc			Connector