



New Trunklinea Plus Batten provide flexibility to customer to choose from 3 CCT and 4 different size and lumen packages, based on their specific need

Trunklinea Plus

The new Philips Trunklinea Plus offers exceptional value. It is Perfect for your everyday lighting installations. Available in 4 standard sizes and 3 CCTs to provide flexibility to customer. It provide quality light and substantial energy and maintenance savings. This new batten range can be used to replace traditional battens with T5 fluorescent lamps.

Benefits

- Slim and trunkable, integrated design
- Polycarbonate housing with one pc extrusion process
- Slim profile: Ideal for task lighting / cove lighting applications

Trunklinea Plus

Features

- 15,000 hrs life, L70/B50
- 1 year warranty
- 4 lengths, 3 colors Increased number of options for easy application
- CRI 70, SDCM < 7, 80lm/W
- Mounting accessories included

Application

- Hospitality
- Offices
- Residential

Versions



Trunklinea Plus BattenL300

Trunklinea Plus BattenL600

Trunklinea Plus BattenL900

Trunklinea Plus BattenL1200

Trunklinea Plus

Application Conditions

Ambient temperature range -20 to +40 °C

Approval and Application

Mech. impact protection code IK02

Ingress protection code IP20

Controls and Dimming

Dimmable No

Operating and Electrical

Input Voltage 220 to 240 V

General Information

CE mark -

Protection class IEC Safety class II

Optical cover/lens type Opal diffuser in polycarbonate cover

Initial Performance (IEC Compliant)

Init. Color Rendering Index >70

Initial LED luminaire efficacy 80 lm/W

Luminous flux tolerance +/-10%

Mechanical and Housing

Color White

Initial Performance (IEC Compliant)

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial luminous flux	Initial input power
911401868080	31600 Trunklinea Plus LED3/WW L300 GM	6500 K	300 lm	4 W
911401868180	31600 Trunklinea Plus LED3/NW L300 GM	4000 K	300 lm	4 W
911401868280	31600 Trunklinea Plus LED3/CW L300 GM	3000 K	300 lm	4 W
911401868380	31600 Trunklinea Plus LED6/WW L600 GM	6500 K	500 lm	7 W
911401868480	31600 Trunklinea Plus LED6/NW L600 GM	4000 K	500 lm	7 W
911401868580	31600 Trunklinea Plus LED6/CW L600 GM	3000 K	500 lm	7 W
911401868680	31600 Trunklinea Plus LED9/WW L900 GM	6500 K	900 lm	10 W
911401868780	31600 Trunklinea Plus LED9/NW L900 GM	4000 K	900 lm	10 W
911401868880	31600 Trunklinea Plus LED9/CW L900 GM	3000 K	900 lm	10 W
911401868980	31600 Trunklinea Plus LED12/WW L1200 GM	6500 K	1100 lm	13 W
911401869080	31600 Trunklinea Plus LED12/NW L1200 GM	4000 K	1100 lm	13 W
911401869180	31600 Trunklinea Plus LED12/CW L1200 GM	3000 K	1100 lm	13 W

