

DIFFUSED CEILING LIGHT FITTING

Diffused Ceiling light fitting is equipped with framed prismatic diffuser. This luminaire is designed for efficient, economical and no-frills illumination of interior spaces and thus blends into the environment effortlessly.

Available in different size options to suit surface and recessed mounted ceilings.

All louvres are located by posi-bolt which allowed them to swing down for luminaire maintenance.

** Picture shown is for illustration purpose only*

DESCRIPTION

Ordering Model	W (mm)	L (mm)	H (mm)	LED Tube
GAC 1202/SU/LED	200	615	90	1 x 2ft
GAC 2212/SU/LED	300	615	90	2 x 2ft
GAC 2222/SU/LED	605	615	90	2 x 2ft
GAC 3222/SU/LED	605	615	90	3 x 2ft
GAC 4222/SU/LED	605	615	90	4 x 2ft
GAC 1414/SU/LED	300	1225	90	1 x 4ft
GAC 2414/SU/LED	300	1225	90	2 x 4ft
GAC 2424/SU/LED	605	1225	90	2 x 4ft
GAC 3424/SU/LED	605	1225	90	3 x 4ft
GAC 4424/SU/LED	605	1225	90	4 x 4ft


* /SU = Surface Mounted

** /LED/1E = One End (L-N), One End (short circuit) LED tube wiring

** /LED/2E = One End (L), One End (N) LED tube wiring

** /LED/SE = Single End (L-N), another End (open circuit) LED tube wiring

PROFILE



Technical Data

Housing	Heavy gauge sheet steel body with fully welded end-cap
Optical	Prismatic diffuser (other options available)
Surface Finishing	White epoxy powder coated & oven baked
Lamp Holder	Polycarbonate housing with Copper plate contact
Wire	Heat resistance 105°C, SIRIM approved material
Connector	UL, VDE safety approved material