

Magnetic Damper absorbs vibration from the ground.



GEO-32MD

GEO-28MD

GEO-24MD

**Automatic Levels**  
Magnetic Damper model

# GEO-MD *series*

**GEO-24MD**  
Magnification: 24X

**GEO-28MD**  
Magnification: 28X

**GEO-32MD**  
Magnification: 32X

## Features

- ❖ Vibration-resistant by magnetic damper
- ❖ Bright and Quality lens  
\* Aperture of GEO-32MD: **40mm**
- ❖ Compact body (Length: **190mm**)
- ❖ Waterproof & Dustproof **IP54**



Aperture



Circular Level



Peep sight



Fine adjustment

## Set Contents



- Auto Level
- Plumb Bob
- Lens Cap
- Adjustment Tools
- Carrying Case

## Option

### Aluminium Tripod SAT series



#### Specifications

Full extended	1,655mm
Full closed	978mm
Weight	3.5kg
Tripod Head	154mm / 66mm

※Quick clamp: Available

Code	Model	Remarks
211501	SAT-OL	Color: Orange
211002	SAT-YL	Color: Yellow

## Specifications

Model		GEO-32MD	GEO-28MD	GEO-24MD
Telescope	Length	190mm		
	Image	Erect		
	Aperture	40mm	30mm	
	Magnification	32X	28X	24X
	Field of view (100m)	1°20'		
	Resolution	3.5"	4.5"	
	Minimum focus	0.50m	0.60m	
	Accuracy (1km double-run leveling)	±1.5mm	±2.0mm	
Graduation	Minimum reading	1°		
Self-leveling	Method	Magnetic		
	Range	±15'		
Circular level	Sensitivity	8' / 2mm		
Weight	Body	1.26kg		
	Case	0.60kg		
IP	Class	IP54		

Code	Model	Remarks
220830	GEO-24MD	Magnification: 24X
220831	GEO-28MD	Magnification: 28X
220832	GEO-32MD	Magnification: 32X

## Myzox Co., Ltd.

401 Yamagoe, Nagakute, Aichi 480-1111 Japan  
TEL : +81-561-64-2210 FAX : +81-561-63-7770

[www.myzoxjapan.com](http://www.myzoxjapan.com)

Your Local Authorized Myzox Dealer is :