# **Water Level Meter**

# ALFA WATER LEVEL METER

#### **BUZZER FUNCTION**

Notify the water level by buzzer and red light.





Probe 13mmφ x 135mm

PRODUCT NAME	MODEL	PKG QTY	MOQ	CODE NO.	C/O
Water Level Meter Type2 30m / 1.5kg	2-30B	1	1	212767	JP
Water Level Meter Type2 50m / 1.8kg	2-50B	1	1	212768	JP
Water Level Meter Type2 100m / 2.6kg	2-100B	1	1	212769	JP

#### **▶ FEATURES**

- · Compact and light body by plastic reel case
- · Smooth rewinding without tangled-up wires
- One-touch battery change
- · Working for water level measuring at dam, drilling well, river & lake

#### **▶ SPECIFICATIONS**

**Dimensions** 

Model	Type2	
Rope	2 core stainless wire rope	
Minimum graduation	10mm	
Outer diameter	$4$ mm $\phi$	
Sensor	Stainless / 13mm  ø	
Reel case	ABS plastic	
Water level detecting	Buzzer & red light	
Power	006P 9V x 1	

The following types are also available.



TYPE1 Buzzer



TYPE3

H260 x D150 x W190mm (30m)

Buzzer and red light Display water temperature 0 ~100°C

# **Water Depth Meter**

## PS-7FL

# EASY OPERATION AND INSTANT MEASUREMENT

For simple and handy check at the construction or survey site.



#### **▶ FEATURES**

- · Press the switch on the case for 2 to 3 seconds and hold the body in the direction of measurement
- · Equipped float sensor and 10m cable enables measurement of remote location easily (PS-7FL)

#### **▶ SPECIFICATIONS**

Model	PS-7FL	PS-7
Channel	1CH	1CH
Depth range	0.6 ~ 80m	0.6 ~ 80m
Detective angle	15°(half of full angle)	24°(half of full angle)
Power	9V (dry cell 006P)	9V (dry cell 006P)
Operating temperature	0 ~ + 50°C	0 ~ + 50°C
Dimension (main unit)	42 x 198mm	42 x 198mm
Dimension (sensor)	50 x 155mm	-
Weight	approx. 170g + 450g	approx. 190g

PRODUCT NAME	MODEL	PKG QTY	MOQ	CODE NO.	C/O
Water Depth Meter 10m cable & Float	PS-7FL	1	1	082294	JP
Water Depth Meter	PS-7	1	1	219316	JP

# **Water Level Meter**

# **WL** series

# TAPE TYPE WATER LEVEL METER

Notify the water level by buzzer.



#### **▶ FEATURES**

- · Able to measure quickly
- Notify by buzzer when probe soak 1cm in water
- · Sensitivity adjustable
- · Self disconnection checking function



## SPECIFICATIONS

-	SPECIFICATIONS	•	
	Model	WL-10M	WL-50M
	Length	10m	50m
	Probe size	19 φ x 140mm	19 φ x 140mm
	Probe weight	100g	100g
	Tape size	12.5 x 0.55mm	12.5 x 0.55mm
	Graduation	2mm each	2mm each
	Material Probe	Stainless	Stainless
	Таре	Fiberglass (non-lead stabilized PVC coating)	Fiberglass (non-lead stabilized PVC coating)
	Case	ABS	ABS
	Power	AA battery x 2	AA battery x 2
	Battery life	24 hours	24 hours
	Case size	219 x 156 x 56mm	354 x 277 x 56mm
	Weight	600g	1,200g

PRODUCT NAME	MODEL	PKG QTY	MOQ	CODE NO.	C/O
Water Level Meter 10m	WL-10M	1	1	216285	JP
Water Level Meter 50m	WL-50M	1	1	102212	JP

STAFF

GNSS ACCESSORY

LASER INSTRUMENT SURVEYING /

10

SURVEYING ACCESSORY

# **Stream Gauge**

# **STREAM GAUGE**

#### STREAMFLOW OBSERVATION

This is for the measurement of flow and storage of water.



AKK design

ΑII

#### **► FEATURES**

- · Made-to-Order
- Durable material of steel, ABS resin & stainless staff
- · Easy to read by clear number
- · Special order can be accepted
- · 3 type of shapes are available



#### **▶ PLATE SHAPE**






Straight



#### Made to Order

- 1. Graduation (Standard / Chuden / AKK)
- 2. Material (Steel / Stainless / ABS)
- 3. Cross-section Surface (U-shape / Round / Straight)
- 4. Grade (Yes / No) \*See below
- 5. Reflective (Yes / No)
  6. Size (Width / Length / Thickness)



PRODUCT NAME	MODEL	PKG QTY	MOQ	CODE NO.	C/O
Stream Gauge	Standard	-	-	102246	JP
Stream Gauge	Chuden	-	-	102254	JP
Stream Gauge	AKK	-	-	102255	JP

# **Water Level Meter**

## **RWL** series

## THIN PROBE

Suitable for small and narrow hole, because of thin probe.



PRODUCT NAME	MODEL	PKG QTY	MOQ	CODE NO.	C/O
Water Level Meter 10M	RWL-10M	1	1	216284	JP
Water Level Meter 50M	RWL-50M	1	1	212108	JP
Water Level Meter 100M	RWL-100M	1	1	212109	JP

# 175mm 12φ ⊥ zero point 30mm

#### **► FEATURES**

- Quick measuring
- Thin probe can be used at small hole
- Self disconnection checking function
- · Notify by buzzer when probe soak at 3cm in the water
- Sensitivity adjustable

▶	SPECIFICA	TIONS		
	Model	RWL-10M	RWL-50M	RWL-100M
	Length	10m	50m	100m
	Tape size	6.20 x 2.0mm	6.20 x 2.0mm	6.20 x 2.0mm
	Graduation	10mm interval	10mm interval	10mm interval
	Probe	12 φ x 175mm	12 φ x 175mm	12 φ x 175mm
	Weight	730g	2,000g	3,100g
	Dimension	219 x 156 x 56mm	333 x 220 x 133mm	333 x 220 x 193mm
	Power	AA battery x 2pcs	AA battery x 2pcs	AA battery x 2pcs