

LED POWER SUPPLY (INDOOR AND OUTDOOR)

KG SERIES (IP20 & IP67)



- Constant Voltage Design
- Protections: Short Circuit/Overload/Over Voltage/Over Temperature
- Cooling by Free Air Convection
- Small Size, Light Weight and High Efficiency
- 100% Full Load Burn-In Test

CE RoHS

MODEL	POWER	INPUT	OUTPUT		EFFICIENCY	IP	DIMENSION
KG-60-12	60W	AC180-265V	12V	5A	≥80%-85%	IP 20	138*36*25mm
KG-100-12	100W	AC180-265V	12V	8A	≥80%-85%	IP 20	138*50*25mm
KG-150-12	150W	AC180-265V	12V	12.5A	≥80%-85%	IP 20	180*50*25mm
KG-200-12	200W	AC180-265V	12V	16A	≥80%-85%	IP 20	180*50*25mm
KG-300-12	300W	AC180-265V	12V	24A	≥80%-85%	IP 20	185*60*29mm
KG-400-12	400W	AC180-265V	12V	33A	≥80%-85%	IP 20	218*60*29mm
KG-60-24	60W	AC180-265V	24V	2.5A	≥80%-85%	IP 20	138*36*25mm
KG-100-24	100W	AC180-265V	24V	4A	≥80%-85%	IP 20	138*50*25mm
KG-150-24	150W	AC180-265V	24V	6.25A	≥80%-85%	IP 20	180*50*25mm
KG-200-24	200W	AC180-265V	24V	8A	≥80%-85%	IP 20	180*50*25mm
KG-300-24	300W	AC180-265V	24V	12A	≥80%-85%	IP 20	185*60*29mm
KG-400-24	400W	AC180-265V	24V	16A	≥80%-85%	IP 20	218*60*29mm

XLG SERIES (IP20 & IP67)



- Constant Current & Constant Voltage & Constant Power Output Design
- 180-263VAC Input Range, 90-130VAC can be Customized
- Protections: Short Circuit/Overload/Over Voltage/Over Temperature
- Cooling by Free Air Convection
- Fully Protected Aluminium Housing
- Fully Encapsulated with IP67
- Suitable for Dry, Wet and Rainy Environment
- 100% Full Load Burn-In Test
- High Efficiency, Long Life and High Reliability

CE RoHS

MODEL	POWER	INPUT	OUTPUT		EFFICIENCY	IP	DIMENSION
XLG-35-12	35W	AC100-240V	12V	0~3A	≥86.5%	IP67	182*30*20mm
XLG-60-12	60W	AC100-240V	12V	0~5A	≥87.5%	IP67	170*49*34mm
XLG-100-12	100W	AC100-240V	12V	0~8.3A	≥87.5%	IP67	190*49*34mm
XLG-150-12	150W	AC180-263V	12V	0~12.5A	≥90%	IP67	190*49*34mm
XLG-200-12	200W	AC180-263V	12V	0~16.7A	≥92%	IP67	205*69*43mm
XLG-250-12	250W	AC180-263V	12V	0~20A	≥92%	IP67	205*69*43mm
XLG-300-12	300W	AC180-263V	12V	0~25A	≥92%	IP67	240*69*43mm
XLG-35-24	35W	AC100-240V	24V	0~1.45A	≥87.5%	IP67	182*30*20mm
XLG-60-24	60W	AC100-240V	24V	0~2.5A	≥88.5%	IP67	170*49*34mm
XLG-75-24	75W	AC100-240V	24V	0~3.15A	≥88.5%	IP67	170*49*34mm
XLG-100-24	100W	AC100-240V	24V	0~4.2A	≥91%	IP67	190*49*34mm
XLG-120-24	120W	AC100-240V	24V	0~5A	≥91%	IP67	190*49*34mm
XLG-150-24	150W	AC180-263V	24V	0~6.3A	≥87%	IP67	190*49*34mm
XLG-200-24	200W	AC180-263V	24V	0~8.3A	≥88%	IP67	205*69*43mm
XLG-250-24	250W	AC180-263V	24V	0~10A	≥92%	IP67	205*69*43mm
XLG-350-24	350W	AC180-263V	24V	0~14.5A	≥92%	IP67	240*69*43mm
XLG-400-24	400W	AC180-263V	24V	0~16.5A	≥92%	IP67	240*69*43mm
XLG-500-24	500W	AC180-263V	24V	0~20.8A	≥92%	IP67	205*120*56mm
XLG-600-24	600W	AC180-263V	24V	0~25A	≥91.5%	IP67	235*120*56mm