

# ZECITH LED Highbay



## LED & Optical

- Output Range : 3000 – 28500lm
- Photometric Options : Type II
- System Efficacy : Up to 150LPW
- CCT : 4000K/5000K @ 70CRI
- Operation Temp : -10 ~ 40°C

## Electrical

- Input voltage : 220-240 V<sub>AC</sub>
- Input Frequency :50/60Hz
- Power Factor >0.9
- IP Rated : IP65

## Construction & Finishing

- Die Cast housing with polyester powder paint, Standard colors: Grey

## Applications

- Road way
- Pathway




## Warranty

- System Warranty : 5 Year
- Certification : CE \ CB certified

## Order Description:

Order Logic	Watt (W)	Voltage (V)	CCT	Lumen Output	LPW	P.F	Dimension (D x H)	Internal SPD	Lifetime (Hrs)	Qty/Ctn
ZCHBW100WA0GR0	100	220-240	4000K	12,000	120	> 0.9	280 X 193	> 10kV	50K	1pcs/Box
ZCHBW150WA0GR0	150	220-240	4000K	20,000	135	> 0.9	280 X 203	> 10kV	50K	1pcs/Box
ZCHBW200WA0GR0	200	220-240	4000K	27,000	135	> 0.9	280 X 218	> 10kV	50K	1pcs/Box

## Product Dimension:



## Photometric:

