



# Series variation



# Micro cylinder CMA2 series

- SCP\*3
- CMK2
- CMA2**
- SCM
- SCG
- SCA2
- SCS2
- CKV2
- CAV2/  
COVPIN2
- SSD2
- SSG
- SSD
- CAT
- MDC2
- MVC
- SMG
- MSD/  
MSDG
- FC\*
- STK
- SRL3
- SRG3
- SRM3
- SRT3
- MRL2
- MRG2
- SM-25
- ShkAbs
- FJ
- FK
- Spd  
Contr
- Ending

Variation	Model No.  JIS symbol	Bore size (mm)	Standard stroke length (mm)									Min. stroke length (mm)	Max. stroke length (mm)	Available stroke length (mm)
			25	50	75	100	150	200	250	300				
			Double acting/ single rod	CMA2 	φ20 φ30 φ40	●	●	●	●	●	●			
Double acting/ direct	CMA2-E 	φ20/φ30/φ40	●	●	●	●	●	●	●	●	1	700	700	

●: Standard, ◎: Option, ○: Custom order, ■: Not available

	Custom stroke length (per mm)	Mounting									Option					Accessory			Switch	Page	
		Basic	Axial foot		Rod side flange	Head side flange	Eye bracket	Clevis bracket	Rod side trunnion	Head side trunnion	Bellows (100°C)	Bellows (250°C)	Piston rod material change	Same port position	Copper and PTFE free	Rod eye	Rod clevis	Clevis bracket			
		00	LB	LS	FA	FB	CA	CB	TA	TB											J
1	●	●	●	●	●	●	●	●	●	●	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	194
1	■	■	●	●	■	■	■	■	■	■	■	■	◎	■	■	◎	◎	◎	◎	208	

SCP\*3

CMK2

CMA2

SCM

SCG

SCA2

SCS2

CKV2

CAV2/  
COVP/N2

SSD2

SSG

SSD

CAT

MDC2

MVC

SMG

MSD/  
MSDG

FC\*

STK

SRL3

SRG3

SRM3

SRT3

MRL2

MRG2

SM-25

ShkAbs

FJ

FK

Spd  
Contr

Ending