


Series variation



Compact cylinder SSG Series

●: Standard, ◎: Option, ■: Not available

Variation	Model No. JIS symbol	Bore size (mm)	Stroke length (mm)												Max. stroke length (mm)	Min. stroke length (mm)	Switch	Page
			5	10	15	20	25	30	35	40	45	50	75	100				
With double acting/ single rod switch, with 2-color display, off-delay, T1 switch	SSG SSG-L SSG-L1 	φ12/φ16	●	●	●	●	●	●							30	1	◎	1052
		φ20/φ25	●	●	●	●	●	●	●	●	●	●			50			
		φ32/φ40	●	●	●	●	●	●	●	●	●	●	●	●	100			
		φ50/φ63/φ80/φ100	■	●	●	●	●	●	●	●	●	●	●	●	100			

- SCP*3
- CMK2
- CMA2
- SCM
- SCG
- SCA2
- SCS2
- CKV2
- CAV2/
COVP/IN2
- SSD2
- SSG**
- SSD
- CAT
- MDC2
- MVC
- SMG
- MSD/
MSDG
- FC*
- STK
- SRL3
- SRG3
- SRM3
- SRT3
- MRL2
- MRG2
- SM-25
- ShkAbs
- FJ
- FK
- Spd
Contr
- Ending