



Safety Data Sheet

Page 1 of 9

LOCTITE SF 7452 known as 7452 1.75oz glass botl EN/CH/JP

SDS No. : 153559

V002.4

Revision: 09.03.2018

printing date: 06.07.2018

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE SF 7452 known as 7452 1.75oz glass botl EN/CH/JP

Other means of identification: LOCTITE SF 7452 1.75OZEN/CH/JP

Product code: IDH706653

Recommended use of the chemical and restrictions on use

Intended use: Primer

Identification of manufacturer, importer or distributor

Importer: Henkel Malaysia Sdn Bhd 46th Floor, Menara TM, Jalan Pantai Baharu, 59200 Kuala Lumpur, Malaysia. Phone :+ 603 22461000 Fax : + 60322461188

E-mail address of person responsible for Safety Data Sheet: ap-ua-psra.sea@henkel.com

Emergency information: FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call CHEMTREC: +1 703-741-5970

Section 2. Hazards identification

GHS Classification:

<u>Hazard Class</u>	<u>Hazard Category</u>	<u>Target organ</u>
Flammable liquids	Category 2	
Serious eye damage/eye irritation	Category 2	
Specific target organ toxicity - single exposure	Category 3	Central Nervous System

GHS label elements:

Hazard pictogram:



Signal word:

Danger

Hazard statement: H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precaution:

Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response: P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage: P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.

Disposal: P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Section 3. Composition / information on ingredients

Substance or Mixture:
Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
Acetone 67-64-1	60- 100 %	Flammable liquids 2 H225 Serious eye damage/eye irritation 2 H319 Specific target organ toxicity - single exposure 3 H336
N,N-Dimethyl-p-toluidine 99-97-8	0.1- 1 %	Acute toxicity 4; Oral H302 Acute toxicity 3; Dermal H311 Carcinogenicity 1B H350 Specific target organ toxicity - repeated exposure 2 H373 Chronic hazards to the aquatic environment 3 H412

Section 4. First aid measures

Inhalation:	Move to fresh air. If symptoms persist, seek medical advice.
Skin contact:	Rinse with running water and soap. Seek medical advice.
Eye contact:	Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.
Ingestion:	Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting. Seek medical advice.
Indication of immediate medical attention and special treatment needed:	See section: Description of first aid measures

Section 5. Fire fighting measures

Suitable extinguishing media:	Carbon dioxide, foam, powder
Specific hazards arising from the chemical:	In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO ₂) can be released. Do not expose to direct heat. See section 10.
Special protection equipment and precautions for firefighters:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Hazardous combustion products:	Oxides of carbon, oxides of nitrogen, irritating organic vapors.
Additional fire fighting advice:	In case of fire, keep containers cool with water spray.

Section 6. Accidental release measures

Personal precautions:	Avoid skin and eye contact. Ensure adequate ventilation. Wear protective equipment.
Environmental precautions:	Do not let product enter drains.
Clean-up methods:	For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal. Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Handling:	Use only in well-ventilated areas. Vapours should be extracted to avoid inhalation. Keep away from sources of ignition - no smoking. Take measures to prevent the build-up of electrostatic charges.
Storage:	Store in a cool, well-ventilated place. Keep away from heat and direct sunlight.

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

ACETONE 67-64-1	Value type	Time Weighted Average (TWA):
	ppm	250
	Remarks	ACGIH
ACETONE 67-64-1	Value type	Time Weighted Average (TWA):
	ppm	500
	mg/m³	1,187
	Remarks	MY OEL
ACETONE 67-64-1	Value type	Short Term Exposure Limit (STEL):
	ppm	500
	Remarks	ACGIH

Respiratory protection: Ensure adequate ventilation.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A (EN 14387)

Hand protection: Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection: Wear protective glasses.
Protective eye equipment should conform to EN166.

Body protection: Wear suitable protective clothing.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Engineering controls: Ensure good ventilation/extraction.

Hygienic measures: Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working. Good industrial hygiene practices should be observed.

Section 9. Physical and chemical properties

Appearance: colourless
liquid
Odor: Acetone
Odor threshold (CA): No data available.
pH: Not applicable
Melting point / freezing point: No data available.

Specific gravity: 0.7926
Boiling point: 57 °C (134.6 °F)
Flash point: -17 °C (1.4 °F)
 (Tagliabue closed cup)
Evaporation rate: No data available.
Flammability (solid, gas): No data available.
Lower explosive limit: No data available.
Upper explosive limit: No data available.
Vapor pressure: 185 mm hg
 (; 20 °C (68 °F))
Vapor density: Heavier than air
Density: 0.79 g/cm3
Solubility: No data available.
Partition coefficient: n-octanol/water: No data available.
Auto ignition: No data available.
Decomposition temperature: No data available.
Viscosity: No data available.

VOC content: 100 %
 (2010/75/EC)

Section 10. Stability and reactivity

Reactivity/Incompatible materials: Reaction with strong acids.
 Reacts with strong oxidants.
Chemical stability: Stable under recommended storage conditions.
Conditions to avoid: No decomposition if used according to specifications.
Hazardous decomposition products: Irritating organic vapours.

Section 11. Toxicological information

Oral toxicity: Acute toxicity estimate (ATE) : > 2,000 mg/kg
 Method: Calculation method

Inhalative toxicity: Acute toxicity estimate (ATE) : > 20 mg/l
 Exposure time: 4 h
 Test atmosphere: Vapor.
 Method: Calculation method

Dermal toxicity: Acute toxicity estimate (ATE) : > 2,000 mg/kg
 Method: Calculation method

Symptoms of Overexposure: EYE: Irritation, conjunctivitis.
 Vapors may cause drowsiness and dizziness.
 Prolonged or repeated contact may cause skin irritation.

Acute oral toxicity:

Acetone 67-64-1	Value type	LD50
	Value	5,800 mg/kg
	Species	rat
	Method	not specified

Acute inhalative toxicity:

Acetone 67-64-1	Value type	LC50
	Value	76 mg/l
	Exposure time	4 h
	Species	rat
	Method	not specified

Acute dermal toxicity:

Acetone 67-64-1	Value type	LD50
	Value	> 15,688 mg/kg
	Species	rabbit
	Method	Draize Test

Skin corrosion/irritation:

Acetone 67-64-1	Result	not irritating
	Exposure time	
	Species	guinea pig
	Method	not specified

Serious eye damage/irritation:

Acetone 67-64-1	Result	irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Acetone 67-64-1	Result	not sensitising
	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	not specified

Germ cell mutagenicity:

Acetone 67-64-1	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Acetone 67-64-1	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Acetone 67-64-1	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Acetone 67-64-1	Result	negative
	Type of study / Route of administration	oral: drinking water
	Metabolic activation / Exposure time	
	Species	mouse
Method	not specified	

Repeated dose toxicity:

Acetone 67-64-1	Result	NOAEL=900 mg/kg
	Route of application	oral: drinking water
	Exposure time / Frequency of treatment	13 wdaily
	Species	rat
	Method	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Section 12. Ecological information

Ecotoxicity: Do not empty into drains / surface water / ground water.

Toxicity:

Acetone 67-64-1	Value type	LC50
	Value	8,120 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Pimephales promelas
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Acetone 67-64-1	Value type	EC50
	Value	8,800 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia pulex
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Acetone 67-64-1	Value type	NOEC
	Value	530 mg/l
	Acute Toxicity Study	Algae
	Exposure time	8 d
	Species	Microcystis aeruginosa
	Method	DIN 38412-09
Acetone 67-64-1	Value type	EC10
	Value	1,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	Pseudomonas putida
	Method	DIN 38412, part 27 (Bacterial oxygen consumption test)
N,N-Dimethyl-p-toluidine 99-97-8	Value type	LC 50
	Value	46 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Fathead minnow (Pimephales promelas)
	Method	

Persistence and degradability:

Acetone 67-64-1	Result	readily biodegradable
	Route of application	aerobic
	Degradability	81 - 92 %
	Method	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)

Bioaccumulative potential / Mobility in soil:

Acetone 67-64-1	LogPow	-0.24
	Temperature	
	Method	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
N,N-Dimethyl-p-toluidine 99-97-8	LogPow	2.81
	Temperature	25 °C
	Method	not specified

Section 13. Disposal considerations

Product

Method of disposal: Dispose of in accordance with local and national regulations.

Packaging

Disposal of uncleaned packages: Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road transport ADR:

Class: 3
Packing group: II
Classification code: F1
Hazard ident. number: 33
UN no.: 1090
Label: 3
Technical name: ACETONE (solution)

Railroad transport RID:

Class: 3
Packing group: II
Classification code: F1
Hazard ident. number: 33
UN no.: 1090
Label: 3
Technical name: ACETONE (solution)

Inland water transport ADN:

Class: 3
Packing group: II
Classification code: F1
Hazard ident. number: 33
UN no.: 1090
Label: 3
Technical name: ACETONE (solution)

Marine transport IMDG:

Class: 3
Packing group: II
UN no.: 1090
Label: 3
EmS: F-E ,S-D
Seawater pollutant: -
Proper shipping name: ACETONE (solution)

Air transport IATA:

Class: 3
Packing group: II
Packaging instructions (passenger): 353
Packaging instructions (cargo): 364
UN no.: 1090
Label: 3
Proper shipping name: Acetone (solution)

Section 15. Regulatory information

Regulatory Information: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013 [P.U.(A) 310/213]
Industry Code of Practice on Chemicals Classification and Hazard Communication

Global inventory status:

Regulatory list	Notification
EINECS	yes
TSCA	yes
AICS	yes
ENCS (JP)	yes
KECI (KR)	yes
IECSC	yes
ISHL (JP)	yes

Section 16. Other information

Disclaimer:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.