



JY-9999 High Pressure Injection Grout Machine



Product Description

JY-9999 is one-component grouting injector which is used to inject epoxy or polyurethane filling materials to water-leaking cracks.

JY-9999 can generate a working pressure of 15000psi only within 10 seconds. Portable body, weighing only 9kg, easy to carry & maintain, maximum output pressure up to 15000psi. The fault can be self-maintenance during site operation. The medicament can also be injected into small cracks and pores (larger than 0.01mm).

JY-9999 is a professional Injector Pump in the field of filling resin into the concrete structure.

Since it is manufacturer to be small-sized and light-weighted, it can be an essential device at a concrete repair site.

Scope of Application

Leak-stoppage, waterproof & reinforcement for concrete structure, such as basement, floor, the second joints, subway, tunnel, Continuous wall, cracks, water seepage, etc.



Material Application

Pu foam stop leakage agent, Epoxy resin, non-granular mobile-liquid.

Specifications

Weight	9 kg
Maximum output pressure	15000psi
Pressure of starting again	Less than 8000psi
Safe range of high-pressure hose	Less than 10000psi
Safe range of switch valve	Less than 15000psi

Accessories

Drill	1 set China drill 910w
High pressure hose	1 pc 5M
Shut-off valve	1 set
Repairing kit	1 set
O-ring set	1 set
T type wrench	1 set
Filter	1 pc
Material cup	1 set