

# TSD-5MPL-2104/2108 - 4/8/16 CH Hybrid DVR



**4/8/16 CH    DVR**  
**USB    H.265    5MP**  
**2-Way Audio    DDNS    CMS**

## Features

- 4/8 CH DVR supports TVI/AHD/CVI 5MP/4MP/1080P/720P/ WD1 video input
- 16 CH DVR supports TVI/AHD/CVI 5MP/4MP/1080P video input
- 4/8/16 CH DVR supports 2/4/8 CH 5MP/4MP/3MP/1080P/960P/720P IP video input by default
- 4 CH DVR: 4 CH analog video input can be switched to 4CH IP video input
- 8 CH/16 CH DVR: 8 analog video input can be switched to 8CH IP video input
- Adopt standard h.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphics User Interface (GUI), window style operation by mouse
- Multi-mode recording: annual/timed/motion/AI recording
- Playback: 4/8/16 CH simultaneously playback
- Search: time slice, time, event, tag search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PoE network protocol
- Remote control via Web or CMS: preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Authorization management, log review and device status review
- Support 1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presents and 8 cruises
- Support NAT function and QR Code scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Android OS

Model	TSD-5MPL-2104/2108
Channel	4/8/16CH IPC Audio
Support	4MP, 5MP, 3MP, 1080p, 960p, 720p @30fps
Audio	1 CH local audio in/out
Network	RJ45 100Mbps
Video	5MP@30fps
Output	-10°C ~ 50°C, 10~90% (Humidity)
Working Environment	4/8/16 CH Playback
Power	12VDC, <10W w/o HDD (Adapter Included)
Dimensions	255(W) 42(H) 222(D)mm