Advance Lube Enterprise(565982-T) HS(M) 3745, PTD 153751, Jln Berjaya 8, Tmn Perindustrian Berjaya, Kempas Lama, J.B, Johor, Malaysia Tel: +607-5543000 Fax:+607-5541212

## DATA SHEET



## **CERTIFICATE OF ANALYSIS**

CHEMICAL & PHYSICAL PROPERTIES:

PRODUCT	ENGINE OIL
GRADE	SAE 10W40 SEMI SYN SM (ISUZU TROOPER)
VOLUME	1L
DATE OF ANALYSIS	13 JAN 2020
BATCH NO. OF SAMPLE	QA1810204

## ANALYSIS RESULT:-

Characteristics Method	Unit	Method	Result	Specification	
				Min	Max
Kinematic Viscosity @ 100°C	cSt	ASTM D445	14.5		
Kinematic Viscosity @ 40°C	cSt	ASTM D445	97.6	Report	
Viscosity Index	cSt	ASTM D2770	154.0	-	-
Total Base Number	mgKOH/g	ASTM D2896	7.3	-	-
Specific Gravity @ 15°C	kg/m³	ASTM D4052	0.87	0.86	0.90
Flash Point	°C	ASTM D93	235	>210	-
Color	-	ASTM D1500	3.0	<0.5	>3.0
Appearance	-	Visual	Bright & Clear	Report	
Sulphated Ash %wt.		<0.01			

The data reported on this Document have been electronically validated.