

Power Up PAO/Ester Racing Oil

Product Description:

Power Up Racing Oil Fully Syn SN Series is blended with highest quality additive and base stock. It is a premium quality "Mid SAPS" lubricant used for racing and general purpose driving. It is formulated with high quality Polyalphaolefins (PAO) and group v ester base fluid and the high technology core additive package that meets the requirements of ACEA C3 and MB APPROVAL 229.51. It is suitable for use in wide range of modern passenger cars and racing vehicles which runs on high torque and BHP.

Applications / Benefits:

1. Ensures maximum engine performance and power.
2. Highly recommended for both smaller engines and high performance bigger engines capacity
3. Recommended Min. 12,000km per oil change, but not more than 17,000km. (This is subjected to engine in good condition, for worn out engine shorter mileage per oil change).
4. Reduces carbon, acid and sludge formations.
5. Ensures smoother, cooler and quieter engines.
6. Increase the power of the engine.
7. Keeps engine running clean and efficient.
8. Ensure Cleaner engine after usage.

Typical Characteristics:

Test Description	Method	5W20	5W30	5W40	10W50	0W-20	0W-40
SAE Viscosity Grade	SAE J 300						
Specific Gravity @ 15 °C	ASTM D 4052	0.847	0.850	0.855	0.850	0.848	0.856
Flash Point, °C	ASTM D 92	212	214	216	230	216	226
Pour Point , °C	ASTM D 97	-39	-39	-39	-39	-42	-45
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	47.7	70.1	91.9	102	44.6	75.5
cSt @ 100°C	ASTM D 445	8.5	11.8	14.5	16.5	8.33	13.6
Viscosity Index	ASTM D 2270	156	165	164	166	165	185
TBN, mgKOH/g	ASTM D 2896	7.8	7.8	7.8	7.8	7.8	10
Color	ASTM D 1500	<2.5	<2.5	<2.5	<2.5	2.5	<3.5
CCS, cP	ASTM D 5293	5318	5215	5536	5568	5536	5536

Specifications, Approvals & Recommendations:

- API SN
- ACEA A1/B1-12
- ACEA A5/B5-12
- ACEA C2-12
- ACEA C3-12
- ACEA A3/B3-08
- ACEA A3/B4-08