

HD 40 CF/SF

Product Description

Heavy Duty MONO 40 CF/SF is formulated with high viscosity index hydrogenated base oils and of low-ash additive system. It is specially designed to meet the performance needs of modern highly rated, mainly used as for the purpose of top-up.

REDEFINING LIQUID ENGINEERING

Performance Benefits

Good anti-foam, anti-wear and anti-corrosion properties	
Good Anti-wear protection	
Good dispersancy and detergency technology	

Applications

TESTING METHODS	RESULTS
SAE GRADE	40
VISCOSITY, ASTM D445	
cSt @ 40 °C	92
cSt @ 100 °C	14.91
Viscosity Index, ASTM D 2270	92
Sulfanated Ash, Wt%, ASTM D874	0.47
Total Base # , mg KOH/g, ASTM D 2896	3
Pour Point, °C, ASTM D 97	-20
Flash Point, °C, ASTM D 92	244
Density @ 15°C kg/l, ASTM D 4052	0.895

Approval

PRODUCTS AVAILABLE IN 18L, 200L

Health, Safety & Environment

Health and Safety

- Our Lubricant is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
- Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.
- Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.advancelubholdings.com>
- Protect the Environment Take used oil to an authorized collection point.
- Do not discharge into drains, soil or water. Additional Information Advice on applications not covered here may be obtained from our representative.