

SAE 50 CF

Description

ENGINE OIL CF 50 is a heavy-duty diesel engine oil developed to meet the requirements of a variety of diesel engines operating under severe conditions. ENGINE OIL CF 50 is suitable for use in a wide range of on- and off-highway applications where an API CF oil is recommended. ENGINE OIL CF 50 is based on high quality refined virgin base oil in combination with a special additive package to ensure the quality is top notch. Monograde is often used as top-up purpose and not recommended for oil change usage.

REDEFINING LIQUID ENGINEERING

Performance Benefits

High thermal and oxidation stability

Effective in preventing from wear, corrosion and foam

TESTING METHODS	RESULTS
SAE GRADE	50
VISCOSITY, ASTM D445	
cSt @ 40 °C	148.9
cSt @ 100 °C	14.8
Viscosity Index, ASTM D 2270	129.8
Sulfanated Ash, Wt%, ASTM D874	1.5
Total Base # , mg KOH/g, ASTM D 2896	1
Pour Point, °C, ASTM D 97	-15
Flash Point, °C, ASTM D 92	225
Density @ 15°C kg/l, ASTM D 4052	0.89

Approval

Exceeds: API CF/SF, MTU Type 2, CCMC G2/D1, MIL-L-46152

PRODUCTS AVAILABLE IN 5L, 18L, 200L

Health, Safety & Environment

Health and Safety

- Our Lubricant is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
- Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.
- Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.advancelubholdings.com>
- Protect the Environment Take used oil to an authorized collection point.
- Do not discharge into drains, soil or water. Additional Information Advice on applications not covered here may be obtained from our representative.