

UTTO 80W (10W30 UTTO)

Description

UNIVERSAL TRACTOR POWER SYN 80W is a high performance fluid for use in (CVT) transmissions, hydraulic systems, oil immersed brakes of tractors and off-road equipment. These fluids are specially designed for use where a common lubricant reservoir serves transmissions, final drives and hydraulic systems and to optimize the performance of agricultural and commercial tractors. This product can also be used where a 10W-30 UTTO product is recommend.

REDEFINING LIQUID ENGINEERING

Performance Benefits

Excellent high Load Carrying Ability	Specification meets up to GL4
High EP Performances	Superior Thermal Stability
Long Lasting protection under Scuffing, Spalling and Pitting situation	Superior Oxidation Stability

TESTING METHODS	RESULTS
SAE GRADE	80W
VISCOSITY, ASTM D445	
cSt @ 40 °C	51.7
cSt @ 100 °C	9.7
Viscosity Index, ASTM D 2270	175
Sulfanated Ash, Wt%, ASTM D874	0.37
Total Base # , mg KOH/g, ASTM D 2896	7.0
Pour Point, °C, ASTM D 97	-22
Flash Point, °C, ASTM D 92	260
Density @ 15°C kg/l, ASTM D 4052	0.86

Approval

*API GL-4 John Deere J20C, J20D ZF TE ML-06B/D/E/F/H/M Volvo WB101 (97303)
MF M1145 AGCO CVT ML200 Case MS 1204/6/7/9 Fendt Vario
Allison C-4 Valtra G2-08 (XT-60) Valtra G2-10 (XT-60+) Caterpillar TO-2
Claas CVT MAT 3540 (CVT) CNH MAT 3525/3526 NH410B, NH420A
Ford M2C134D Ford M2C86A/B New Holland 82948718 Oliver: Type 55/Type 5J
Eaton I-280-S I.H.C: B-5 & B-6 Hydran White: Q-1705/1722/1766B White: Q-1802/1826
Eaton M2950S Kubota: UDT fluid Sauer Sundstrand/ Danfoss Denison HF(-0-2)
JCMAS HK P-041 DIN 51524-3
PRODUCTS AVAILABLE IN 5L, 18L, 200L*

Health, Safety & Environment

Health and Safety

- Our Lubricant is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
- Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.
- Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.advancelubholdings.com>
- Protect the Environment Take used oil to an authorized collection point.
- Do not discharge into drains, soil or water. Additional Information Advice on applications not covered here may be obtained from our representative.