

GL4 EP 90

Description

GL-4 EP 90 oils are high performance, multipurpose, thermally stable, extreme pressure automotive hypoid gear oils formulated to exceed the severe API GL-4 performance standard. It is designed and manufactured from selected premium quality base oils and specially selected additives system to provide excellent protection for heavy-duty manual transmission of heavily loaded equipment and passenger vehicles.

REDEFINING LIQUID ENGINEERING

Performance Benefits

Excellent high Load Carrying Ability	Specification meets up to GL5 and GL4
High EP Performances	Superior Thermal Stability
Long Lasting protection under	Superior Oxidation Stability
Scuffing, Spalling and Pitting situation	

TESTING METHODS	RESULTS
SAE GRADE	90
VISCOSITY, ASTM D445	
cSt @ 40 °C	112
cSt @ 100 °C	14.8
Viscosity Index, ASTM D 2270	137
Sulfanated Ash, Wt%, ASTM D874	0.37
Total Base # , mg KOH/g, ASTM D 2896	12
Pour Point, °C, ASTM D 97	-30
Flash Point, °C, ASTM D 92	210
Density @ 15°C kg/l, ASTM D 4052	0.89

Approval



PRODUCTS AVAILABLE IN 5L, 18L, 200L

Health, Safety & Environment

Health and Safety

- Our Lubricant is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
- Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.
- Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from http://www.advancelubeholdings.com
- Protect the Environment Take used oil to an authorized collection point.
- Do not discharge into drains, soil or water. Additional Information Advice on applications not covered here may be obtained from our representative.