

Power Up Gear and Bearing Oil

Product Description:

Power Up industrial gear and bearing oil are formulated with synthetic base oil with performance additive that enhance oxidation stability, improve foam control, maintain superior stability in the presence of water and provide protection against rust, corrosion and wear. Synthetic base oil provide longer oil life over conventional mineral.

Applications / Benefits:

- ▯ Naturally high viscosity index, improved low-temperature fluidity, lower operating temperatures
- ▯ Superior anti-wear properties, low traction coefficient, reduced power consumption
- ▯ Better high-temperature oxidation stability, extended lubricant life
- ▯ Outstanding anti-rust and corrosion properties. Improved foam control Superior stability in presence of water (hydrolytic stability and demulsibility)

Typical Characteristics:

Test Description	Method	32	46	68	100	150
ISO Viscosity Grade	-					
Specific Gravity @ 15 °C	ASTM D 4052	0.851	0.855	0.858	0.861	0.865
Flash Point, °C	ASTM D 92	230	232	234	235	235
Pour Point, °C	ASTM D 97	-15	-48	-48	-45	-42
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	31.0	46.0	66.0	97.0	151
cSt @ 100°C	ASTM D 445	5.8	7.7	10.3	13.7	19.7
Viscosity Index	ASTM D 2270	133	136	144	144	145
Color	ASTM D 1500	<0.5	<0.5	<0.5	<0.5	<0.5

Test Description	Method	220	320	460	680	1000
ISO Viscosity Grade	-					
Specific Gravity @ 15 °C	ASTM D 4052	0.871	0.860	0.876	0.861	0.889
Flash Point, °C	ASTM D 92	235	245	255	265	267
Pour Point, °C	ASTM D 97	-42	-39	-39	-39	-33
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	222	321	456	678	995
cSt @ 100°C	ASTM D 445	25.8	35.2	47.4	63.5	78.2
Viscosity Index	ASTM D 2270	148	155	162	164	160
Color	ASTM D 1500	<0.5	<0.5	<0.5	<0.5	<1.0