

CHAINSAW OIL 100

Description

Chainsaw Oil is specifically developed for the lubrication of chain and guide bars of modern chain saws. Selected mineral base oils are combined with special additives to provide good protection against wear, rust and corrosion. Chainsaw Oil has good low temperature flow properties which makes it suitable for outside applications even during the winter season.

REDEFINING LIQUID ENGINEERING

Performance Benefits

Thermal Oxidation stability	Stays well in place on saw chains and guide bars and ensures optimum component lifetime
Good Adherence of metal surface	Contribution toward increased chain and guide bar life and reduced maintenance costs as wear related failures are reduced
Low Pour Point	Ensure Flow Ability even at lower operating temperature

Applications

Chainsaw Oil can be used in hand-held or machine operated chain saws as specified by the manufacturer. It is suitable for lubrication of chains, slideways and guides in industrial applications, where a lubricant with good adherence, protection against wear, rust and corrosion and a low pour point is required.

TESTING METHODS	RESULTS
SAE GRADE	Chainsaw oil 100
VISCOSITY, ASTM D445	
cSt @ 100 °C	11.0
Pour Point, °C, ASTM D 97	-25



Flash Point, °C, ASTM D 92

220

Density @ 15°C kg/l, ASTM D 4052

0.87

Health, Safety & Environment

Health and Safety

- Our Lubricant is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
- Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.
- Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.advancelubholdings.com>
- Protect the Environment Take used oil to an authorized collection point.
- Do not discharge into drains, soil or water. Additional Information Advice on applications not covered here may be obtained from our representative.