

SAE 10W-40 CF4

Description

2T TC PREMIUM is a premium quality motorcycle oil recommended for Kawasaki, Suzuki and Yamaha motorcycles as well as other two-stroke gasoline engines. It provides better engine protection even at its low recommended dosage, assuring longer engine life

REDEFINING LIQUID ENGINEERING

Performance Benefits

Thermal Oxidation stability	
Excellent detergency/ dispersancy	
Environmentally friendly cleaner exhaust emission	

Applications

It is designed as per requirement of Engine oil for use in BS I/ BS II Commercial vehicle diesel engines manufactured by Tata Motors.

TESTING METHODS	RESULTS
SAE GRADE	2T TC
VISCOSITY, ASTM D445	
cSt @ 40 °C	88
cSt @ 100 °C	11.4
Viscosity Index, ASTM D 2270	104
Sulfanated Ash, Wt%, ASTM D874	N/A
Total Base # , mg KOH/g, ASTM D 2896	1.2
Pour Point, °C, ASTM D 97	-18
Flash Point, °C, ASTM D 92	248

Usage

Fuel (in liters)	2T Premium (in ml)
1 liter	25 ml
2 liters	50 ml
3 liters	75 ml
4 liters	100 ml
5 liters	125 m

Health, Safety & Environment

Health and Safety

- Our Lubricant is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
- Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.
- Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.advancelubholdings.com>
- Protect the Environment Take used oil to an authorized collection point.
- Do not discharge into drains, soil or water. Additional Information Advice on applications not covered here may be obtained from our representative.