Power Excel Sdn Bhd (Co. No. 676329-D) HS(M) 3745, PTD 153751, Jalan Berjaya 8, Taman Perindustrian Berjaya Kempas Lama, 81200 Johor Bahru, Johor, Malaysia Tel :+607-5543000/5583699 Fax :+607-5541212





www.powerup.com.mi

ADV 3323 AMIDOCYANOGEN THIOESTER COMPOUND

PRODUCT DESCRIPTION

- A multifunctional additive.
- Excellent antiwear and extreme pressure property and good antioxidation.
- Has good compatibility with other additives.

PRODUCT FEATURE

- Outstanding extreme pressure performance and antiwear performance.
- Good antioxidation.
- Good compatibility
- Good oil solubility

PRODUCT APPLICATIONS

Used for blending turbine oil, hydraulic oil, gear oil, engine oil, etc. Improve the antioxidation and antiwear performance. Serves as extreme pressure additive in grease. Dosage recommended (wt%): 0.1-4.0%

PRODUCT CHARACTERISTICS

ITEM	TYPICAL VALUE	TEST METHOD
Sulfur, wt%	29-32	SH/T0303
Kinematics Viscosity (100°C), mm ² /s	13.5-15.5	GB/T265
Flash Point (COC), °C	130 min	GB/T3536

PACKING, STORAGE AND TRANSPORTATION

Packed in 200 liter steel drum, 200 kg net weight per drum.
For the details of health and safety precautions, please see the related Material Safety Data Sheet.