

# **HYDRAULIC VG 32**

### Description

HYDRAULIC OIL VG 32 is an universal mineral high grade EP oil for use in heavy duty hydraulic systems and light duty gearboxes, bearings and general lubrication. Not suitable for turbine application. HYDRAULIC OIL VG 32 is formulated with high quality refined mineral base stocks in combination with a special EP-additive technology to achieve the following performance

## **REDEFINING LIQUID ENGINEERING**

#### **Performance Benefits**

Excellent stability against oxidation	High Viscosity Index
Very good protection against wear	Very good foaming propertie
Good water demulsibility	Very effective to rust and corrosion

#### **Applications**

HYDRAULIC OIL VG 32 is formulated with high quality refined mineral base stocks in combination with a special EP-additive technology to achieve the following performance

TESTING METHODS	RESULTS
SAE GRADE	32
VISCOSITY, ASTM D445	
cSt @ 40 °C	32
cSt @ 100 °C	5.5
Viscosity Index, ASTM D 2270	108
Sulfanated Ash, Wt%, ASTM D874	1.0
Total Base # , mg KOH/g, ASTM D 2896	N/A
Pour Point, °C, ASTM D 97	-22

The information contained in this document is based on data believed to be reliable and relates only to matters specifically mentioned in this document. Although all reasonable skill and care is taken in preparation of this information, no representation, warranty or guarantee is made with regards to accuracy, reliability and completeness.



Flash Point, °C, ASTM D 92

235

Density @ 15°C kg/l, ASTM D 4052

0.87

# Approval

Exceeds: AFNOR NFE-48-603, ISO 11158 HV, DIN 51524/3 HVLP, Denison HF-0, Cincinatti P-68, Sauer Danfoss 520L0463, Eaton Vickers M-2950-S/I-386

PRODUCTS AVAILABLE IN 18L, 200L

#### Health, Safety & Environment

Health and Safety

- Our Lubricant is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
- Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.
- Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from http://www.advancelubeholdings.com
- Protect the Environment Take used oil to an authorized collection point.
- Do not discharge into drains, soil or water. Additional Information Advice on applications not covered here may be obtained from our representative.