

SAE 50

Description

SAE 50 is a fuel saving MID SAPS super high-performance universal oil based on synthetic technology designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-4, Euro-5 and Euro-6 engines equipped with a Diesel Particulate Filter (DPF) and suited for diesel engines equipped with EGR and/or SCR after treatment system. It is meant for top-up purpose only.

REDEFINING LIQUID ENGINEERING

Performance Benefits

Thermal Oxidation stability	Control sludge build up and wax formation
Excellent detergency/ dispersancy	Cleaner engines leading to longer life span
High shear stability	Reduce oil consumption through wear and tear

Applications

It is designed as per requirement of Engine oil for use in BS I/ BS II Commercial vehicle diesel engines manufactured by Tata Motors.

TESTING METHODS	RESULTS
SAE GRADE	50
VISCOSITY, ASTM D445	
cSt @ 40 °C	148.9
cSt @ 100 °C	17.6
Viscosity Index, ASTM D 2270	129.8
Sulfanated Ash, Wt%, ASTM D874	1.0
Total Base # , mg KOH/g, ASTM D 2896	N/A

The information contained in this document is based on data believed to be reliable and relates only to matters specifically mentioned in this document. Although all reasonable skill and care is taken in preparation of this information, no representation, warranty or guarantee is made with regards to accuracy, reliability and completeness.



Pour Point, °C, ASTM D 97	-26
Flash Point, ºC, ASTM D 92	235
Density @ 15°C kg/l, ASTM D 4052	0.873

Approval

Approved: Volvo VDS 4.5, Mack EOS-4.5, MB-Approval 228.31 Exceeds: API CF4, ACEA E7/E9, API CK-4, DFS 93K222, DQC III-10-LA, MTU Cat 2. 1, Cummins CES 20086, MAN M3575, Renault RLD-3, CAT ECF-3, Ford M2C171-F 1

PRODUCTS AVAILABLE IN 5L, 18L, 200L

Health, Safety & Environment

Health and Safety

- Our Lubricant is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
- Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.
- Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from http://www.advancelubeholdings.com
- Protect the Environment Take used oil to an authorized collection point.
- Do not discharge into drains, soil or water. Additional Information Advice on applications not covered here may be obtained from our representative.