

SAE 15W-40 CI4 PLUS

Description

ENGINE OIL CI4 PLUS 15W-40 is a high performance semi synthetic engine oil to be used in diesel engines in light- and heavy commercial vehicles with or without turbocharger. ENGINE OIL 15W-40 is designed for use in Euro-II, Euro-III and EURO - IV emission requirements and engines equipped with EGR and/or SCR exhaust after treatment system. ENGINE OIL CI4 PLUS 15W-40 may not been used in diesel engines equipped with a Diesel Particulate Filter (DPF). ENGINE OIL CI4 PLUS 15W-40 is based on high performance synthetic base oil in combination with especially selected additive technology to ensure the following properties.

REDEFINING LIQUID ENGINEERING

Performance Benefits

| Excellent thermal oxidation stability | Extended oil drain interval between 15,000 to 30,000km |
|---|--|
| Excellent protection against forming of bore polishing | Low temperature properties to ensure smooth cold start |
| Suitable for low emission engine equipped with EGR and SCR technology | Excellent protection against wear, foam and corrosion |

| TESTING METHODS | RESULTS |
|--------------------------------------|---------|
| SAE GRADE | 15W-40 |
| VISCOSITY, ASTM D445 | |
| cSt @ 40 °C | 109 |
| cSt @ 100 °C | 14.5 |
| Viscosity Index, ASTM D 2270 | 137 |
| Sulfanated Ash, Wt%, ASTM D874 | 1.35 |
| Total Base # , mg KOH/g, ASTM D 2896 | 12 |
| Pour Point, °C, ASTM D 97 | -30 |



| Flash Point, °C, ASTM D 92 | 230 |
|----------------------------------|------|
| Density @ 15°C kg/l, ASTM D 4052 | 0.88 |

Approval

Exceeds: ACEA E4/E7, API CI4, MB 228.5, MAN M3277, MTU Type 3, Deutz DQC III-10, Volvo VDS- 3, Renault RVI RLD-2, Mack EO-N, Scania LDF-3, DAF extended drain

PRODUCTS AVAILABLE IN 5L, 18L, 200L

Health, Safety & Environment

Health and Safety

- Our Lubricant is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
- Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.
- Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from http://www.advancelubeholdings.com
- Protect the Environment Take used oil to an authorized collection point.
- Do not discharge into drains, soil or water. Additional Information Advice on applications not covered here may be obtained from our representative.