

ATF MATIC S

Description

ATF MATIC S multi-vehicle Automatic Transmission Fluid mainly for Nissan vehicle but also usable for other continental and Asian vehicles, delivering long-lasting shifting performance and component durability for today's automatic transmissions over their standard service life. Its wide coverage of major manufacturer specifications, extensive bench testing and field-testing, makes it suitable for use for virtually all automatic transmissions. For this reason, it reduces the risk of using the wrong oil and simplifies inventory management.

REDEFINING LIQUID ENGINEERING

Performance Benefits

Outstanding anti-shudder performance and smooth shifting	Excellent seal compatibility and conditioning to reduce the risk of fluid leaks from seal shrinkage, hardening and cracking
Excellent resistance to oxidation and thermal breakdown, providing longer fluid life, extended protection and optimal fuel efficiency	Very good foaming properties
Superior cleanliness that keeps the transmission free from sludge and varnish so that the transmission stays clean and functions properly	Very effective to rust and corrosion

Applications

TESTING METHODS	RESULTS
SAE GRADE	32W
VISCOSITY, ASTM D445	
cSt @ 40 °C	25.28
cSt @ 100 °C	5.2

Viscosity Index, ASTM D 2270	N/A
FOAM SEQUAL III @ 24 °C	0
FOAM SEQUAL II @ 93.5 °C	0
Pour Point, °C, ASTM D 97	-15
Foam, Seq I @ 24°C	0
Density @ 15°C kg/l, ASTM D 4052	0.83

Approval

GM DEXRON®-VI

- JASO M315-2013 1A, JASO M315-2013 2A
- JWS 3309, JWS 3314, JWS 3317

Meets Exceeds the performance requirements of:

- Aisin Warner JWS 3309
- ATF RED 1/ RED 1K
- BMW LA2634, LT71141, 7045E, ETL-8072B, MINI T-VI
- Ford MERCON®, Ford FNR5, Ford XT-2-QDX (M), XT-2-QSM (Syn), (XT-8-QAW) JWS 3309, XL-12
- FUSO ATF-II/ATF-SP III/ATF A4
- GM DEXRON® IIIH
- Hino Blue Ribbon ATF
- Honda ATF Z1 (except CVT)
- Hyundai/Kia SP-II/SP-III
- Mazda ATF D-II/ATF M-III/ATF M-V/ATF F-1/ATF S-1/ATF N-1/ATF-3317
- Mitsubishi Diaqueen SK/SP-II/SP-III/J2
- Nissan Matic Fluid C/D/J/K
- Peugeot/Citroen (PSA) AL4
- Renault Matic D2/DPO/AL4
- Subaru ATF/ATF HP/ATF 5AT

PRODUCTS AVAILABLE IN 18L, 200L

Health, Safety & Environment

Health and Safety

- Our Lubricant is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
- Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.
- Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.advancelubeholdings.com>
- Protect the Environment Take used oil to an authorized collection point.
- Do not discharge into drains, soil or water. Additional Information Advice on applications not covered here may be obtained from our representative.

