

## TEXTILE OIL 32 SE

### Description

Compatible with the automatic lubricating systems fitted to most panty-hose knitting machines. It is recommended that the machine manufacturers' guidelines are followed with regard to the oil application rates. It is Self-emulsifiable in water

### REDEFINING LIQUID ENGINEERING

### Performance Benefits

<b>Excellent Stability</b>	<b>Non-corrosive</b>
<b>Formulated to minimize oil splashing</b>	<b>High friction properties</b>
<b>Minimize Misting</b>	<b>Self-emulsifiable in water</b>

### Applications

TESTING METHODS	RESULTS
VG GRADE	32
VISCOSITY, ASTM D445	
cSt @ 40 °C	32
cSt @ 100 °C	N/A
Shelf Life	>7 yrs
Flash Point, Cleveland Open Cup, °C, ASTM D92	>170
Cloud Point °C	<0
Density @ 15°C kg/l, ASTM D 4052	0.86

### Health, Safety & Environment

#### Health and Safety

- Our Lubricant is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.



- Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.
- Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.advancelubholdings.com>
- Protect the Environment Take used oil to an authorized collection point.
- Do not discharge into drains, soil or water. Additional Information Advice on applications not covered here may be obtained from our representative.

**Notes:**

When introducing a new oil to a machine we recommend cleaning the original oil from the machine and oiler unit as thoroughly as possible, to avoid the potential of any incompatibility problems.