

FIBER WALLMOUNT PANEL

- ✓ **Design for indoor type used to provide interconnection between active equipment and outside plant cables in premisses access for commercial and industrial telecommunication.**
- ✓ **Double front door with camlock design to provide security & protection for both side (splice & patch)**
- ✓ **Double compartment separate splice & patching**
- ✓ **Strenght member clamp to avoid cable pull out**
- ✓ **Splice Tray Include to organize fiber and to provide optimum & phsical protection for mechanical splicing method**
- ✓ **Exchange plate for any various type adapter**



MAXI5TMVE

DESCRIPTION	CLM5-FWP-6-XX	CLM5-FWP-12-XX	CLM5-FWP-24-XX	CLM5-FWP-48-XX
	6PORT WFP	12PORT WFP	24PORT WFP	48PORT WFP
PORT	6	12	24	48
MATERIAL	Cold Roll	Cold Roll	Cold Roll	Cold Roll
DIMENSION (WxHxD)	350 x 265 x 44	350 x 265 x 44	350 x 265 x 44	350 x 265 x 102.5
COLOUR	Beige	Beige	Beige	Beige
FINISHED	Epoxy Powder Coated	Epoxy Powder Coated	Epoxy Powder Coated	Epoxy Powder Coated



Closed-Loop Industries SDN. BHD

**NO. 28 & 30, Jalan TS 6/7, Taman Perindustrian Subang,
Taman Indah Subang Uep, 47150 Subang Jaya,
Selangor Darul Ehsan.
+603 - 8081 2216**