



Chassis greases, gas cock greases and rubber greases

Other Greases



Calcium Soap Greases / Gas Cock Greases / Rubber Greases

※1

Classification	Product Name	NLGI (worked penetration) 25°C, 60W	Appearance	Thickener	Base Oil	Kinematic Viscosity of Base Oil 40°C	Approximate Operating Temperature Range	Description	NET, Packing Unit, Code
Calcium Soap Grease	Sumigrease Chassis	No.2 (280)	Yellow-Brown			148mm ² /s	-5 ~ +80°C	Water-resistant calcium soap greases. Ideal for relatively light-duty sliding parts that need to be water resistant, e.g. sliding parts in motor vehicle chassis.	420ml×20 (Code : 266265) 16kg (Code : 266275) 180kg (Code : 266280)
		No.1 (325)		Calcium Soap	Mineral Oil				420ml×20 (Code : 266165) 16kg (Code : 266175) 180kg (Code : 266180)
	Lowtemp Grease	— (269.0W)	Light Brown			15mm ² /s	-50 ~ +80°C	A calcium soap grease formulated with a low-viscosity base oil. Exhibits an excellent low torque effect at low temperatures. Ideal for bearings and sliding parts in machines used in freezers and cold regions.	16kg (Code : 240275)
Gas Cock Grease	Molytone CK	No.1 (330)	Black		Mineral Oil	400mm ² /s	-10 ~ +200°C	A gas cock grease formulated with molybdenum disulfide (MoS ₂) that exhibits excellent gas resistance, as well as torque maintenance, sealing and wear prevention effects, on a sustainable basis. Ideal for cocks consisting of a copper handle and copper body .	500g×6 (Code : 227167) 2.5kg×2 (Code : 227172) 16kg (Code : 227175)
	Molytone CK-S	No.0 (360)		Bentone				A gas cock grease formulated with molybdenum disulfide (MoS ₂) that is designed to form a thick oil film in consideration of the difference between different metals in terms of thermal expansion coefficient and long-term dimension change. Ideal for cocks consisting of a copper handle and aluminum body .	2.5kg×2 (Code : 229072) 16kg (Code : 229075)
	Sumicock SL Grease	No.0 (370)	Ivory		Synthetic Oil	420mm ² /s	-20 ~ +200°C	A gas cock grease formulated with a PTFE additive and a synthetic base oil. It withstands long hours of use. Ideal for push button-operated kitchen gas stoves .	2.5kg×2 (Code : 229672) 16kg (Code : 229675)
Rubber Grease	Moly Rubber Grease	No.1 (315)	Black	Bentone	Special Refined Oil	240mm ² /s	-10 ~ +200°C	A Bentone grease formulated with a special refined oil that is benign to rubber. Excels in wear resistance, anti-seizure and heat resistance performance, thanks to a molybdenum disulfide (MoS ₂) additive.	2.5kg×2 (Code : 245172) 16kg (Code : 245175)
	Sumitec 403	— (300)	White	Lithium Soap	Synthetic Oil	350mm ² /s	-20 ~ +140°C	A lithium soap grease formulated with a synthetic oil that is benign to rubber and excellent in oxidation stability.	16kg (Code : 246075)