



VILLA WATER SUPPLY



LANDED PROPERTIES

FACING WATER PRESSURE PROBLEM AT YOUR HOME??



BATH AND SHOWER



IRRIGATION

Your First Choice Solution Provider

STAY EXCELLENT LIFESTYLE COMFORT FOR YEARS TO COME

CNP is proud to offer the CHLF(T)-PT domestic booster pump. It's designed to maintain a consistent flow with great pressure for your home instant water heater showers, tap, flushing point and garden.

CHLF(T)-PT integrated an automatic feature to provide precise water supply to meet your daily needs and ensure of reliable water pressure even when several taps are turned on simultaneously.

What's more, CNP offers after sales service that provide upkeep while maximizing the warranty provisions.

# LIVING COLLECTION

居家首選好件



# 24 MONTHS WARRANTY



CHLF - PT



CHLF (T) - PT



CHL - PT

## DOMESTIC BOOSTER PUMP



find us on | facebook.

## TECHNICAL DATA

MODEL	SIZE	INLET/OUTLET	POWER (kW)	OUTPUT : m3/hr					
				1.0	1.5	2.0	2.5	3.5	5.0
				DISCHARGE PRESSURE : Bar					
2-30PT	8L	1" / 1"	0.37	2.65	2.45	2.25	1.9	1.2	
2-40PT	18L	1" / 1"	0.55	3.45	3.3	2.9	2.5	1.6	
2-50PT	18L	1" / 1"	0.55	4.3	4.0	3.6	3.15	2.05	
2-60PT	18L	1" / 1"	0.75	5.1	4.8	4.4	3.9	2.4	
4-30PT	18L	1 1/4" / 1"	0.55	2.8	2.74	2.7	2.65	2.48	2.05
4-40PT	18L	1 1/4" / 1"	0.75	3.75	3.66	3.6	3.5	3.23	2.7
4-50PT	18L	1 1/4" / 1"	1.1	4.7	4.61	4.5	4.35	4.0	3.4
4-60PT	18L	1 1/4" / 1"	1.1	5.6	5.52	5.4	5.2	4.88	4.15

## TECHNICAL SPECIFICATIONS

MODEL	MAX. AMBIENT TEMPERATURE	MAX. LIQUID TEMPERATURE	MAX. OPERATING PRESSURE	RECOMMENDED FITTING
2-30PT	Up to +40°C	Up to +70°C	10 bar	🔧 X2 🏠 X1
2-40PT	Up to +40°C	Up to +70°C	10 bar	🔧 X2 🏠 X2
2-50PT	Up to +40°C	Up to +70°C	10 bar	🔧 X4 🏠 X1
2-60PT	Up to +40°C	Up to +70°C	10 bar	🔧 X4 🏠 X2
4-30PT	Up to +40°C	Up to +70°C	10 bar	🔧 X4 🏠 X1
4-40PT	Up to +40°C	Up to +70°C	10 bar	🔧 X4 🏠 X2
4-50PT	Up to +40°C	Up to +70°C	10 bar	🔧 X5 🏠 X3
4-60PT	Up to +40°C	Up to +70°C	10 bar	🔧 X5 🏠 X4

## 5 ADVANTAGES



QUIET OPERATION



LONGER LIFE SPAN



ENERGY SAVING



QUALITY ASSURANCE



EASY INSTALLATION

