

SHIMGE® BWJ/BWJT Series Horizontal Multi-Stage Centrifugal Pump IE2 Motor (Fully stainless steel SUS304)



Model	Power (HP)	Max. Flow L/min	Head Range (mtr)	Voltage (V)	Inlet/Outlet (inch)
BWJ2-3 PC	0.5	58	15.5 ~ 28	240	1" X 1"
BWJ2-4 PC	0.75	58	20.5 ~ 36	240	1" X 1"
BWJ2-5 PC	0.75	58	26.5 ~ 45.5	240	1" X 1"
BWJ2-6 PC	1	58	32 ~ 53.5	240	1" X 1"
BWJ4-3 PC	0.75	116	17 ~ 28	240	1.25" X 1"
BWJ4-4 PC	1	116	23 ~ 37.5	240	1.25" X 1"
BWJ4-5 PC	1.5	116	29 ~ 47	240	1.25" X 1"
BWJ4-6 PC	1.5	116	35.5 ~ 56	240	1.25" X 1"
BWJ2-3	0.5	58	15.5 ~ 28	240	1" X 1"
BWJ2-4	0.75	58	20.5 ~ 36	240	1" X 1"
BWJ2-5	0.75	58	26.5 ~ 45.5	240	1" X 1"
BWJ2-6	1	58	32 ~ 53.5	240	1" X 1"
BWJ4-4	1	116	23 ~ 37.5	240	1.25" X 1"
BWJ4-5	1.5	116	29 ~ 47	240	1.25" X 1"
BWJ4-6	1.5	116	35.5 ~ 56	240	1.25" X 1"
BWJT4-4	1	116	23 ~ 37.5	415	1.25" X 1"
BWJT4-6	1.5	116	35.5 ~ 56	415	1.25" X 1"
BWJT8-3	1.5	183	23 ~ 29.5	415	1.5" X 1.5"
BWJT8-4	2	183	30.5 ~ 39	415	1.5" X 1.5"
BWJT8-5	3	183	39.5 ~ 51	415	1.5" X 1.5"
BWJT16-2	3	367	18 ~ 26	415	1.5" X 1.25"

BW(T), BWJ(T) stainless steel horizontal multistage centrifugal pumps are non self-priming pumps
 Overflowing parts of pump made of stainless steel 304. Protection class: IP55, Insulation class: F
 Hard alloy and fluorine rubber mechanical seal. Liquid temperature up to 68°C for standard type
 Ambient temperature up to 40°C, Maximum working pressure: 10 bar

