Sikafloor®-3 QuartzTop Dark Green



SECTION 1: Identification of the hazardous chemical and of the supplier

Product name : Sikafloor®-3 QuartzTop Dark Green

Product code 000000606625

Type of product : solid

Manufacturer or supplier's details

Company : Sika Kimia Sdn. Bhd.

Lot 689 Nilai Industrial Estate

71800 Nilai

: +60 6799 1762 Telephone

Telefax : +60 6799 1980

E-mail address : EHS@my.sika.com

Emergency telephone

number

Contact point

SECTION 2: Hazards identification

Classification of the hazardous chemical

Skin corrosion/irritation : Category 2

Serious eye damage/eye

irritation

: Category 1

single exposure

Specific target organ toxicity - : Category 3 (Respiratory system)

Label elements

Hazard pictograms





Signal word : Danger

Hazard statements : H315 Causes skin irritation.

> H318 Causes serious eye damage. H335 May cause respiratory irritation.

Precautionary statements Prevention:

> P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P280 Wear protective gloves/ eye protection/ face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove victim to fresh air

Sikafloor®-3 QuartzTop Dark Green



Version 2.1 SDS Number: 000000606625

and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed. **Disposal:**

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (%)
Quartz (SiO2)	14808-60-7	>= 60 - <= 100
Cement (chromium reduced)	65997-15-1	>= 20 - < 30
chromium (III) oxide	1308-38-9	>= 3 - < 5

SECTION 4: First aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms : irritant effects

Sikafloor®-3 QuartzTop Dark Green

SDS Number: 000000606625 Version 2.1 Revision Date: 05.01.2018

and effects, both acute and

delayed

Cough

Respiratory disorder Excessive lachrymation

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms. Causes skin irritation.

Causes serious eye damage. May cause respiratory irritation.

Notes to physician : Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Physicochemical hazards arising from the chemical

Hazardous combustion

products

: No hazardous combustion products are known

Special protective equipment and precautions for fire-fighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing

methods

: Standard procedure for chemical fires.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

: Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

Environmental precautions : Try to prevent the material from entering drains or water

courses.

Methods and materials for containment and cleaning up : Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage

Handling

Precautions for safe handling

Advice on protection against fire and explosion

Avoid dust formation. Provide appropriate exhaust ventilation

at places where dust is formed.

Sikafloor®-3 QuartzTop Dark Green



Version 2.1 SDS Number: 000000606625 Revision Date: 05.01.2018

Advice on safe handling : Do not breathe vapours/dust.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Follow standard hygiene measures when handling chemical

products

Storage

Conditions for safe storage, including any incompatibilities

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

SECTION 8: Exposure controls and personal protection

Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis	
Quartz (SiO2)	14808-60-7	TWA (Respirable fraction)	0.1 mg/m3	MY PEL	
		PEL (Respirable dust)	0.1 mg/m3	MY PEL	
		TWA (Respirable fraction)	0.025 mg/m3 (Silica)	ACGIH	
Cement (chromium reduced)	65997-15-1	TWA	10 mg/m3	MY PEL	
	Further information: The value is for particulate matter containing no asbestos and <1% crystalline silica				
		PEL (Respirable dust)	5 mg/m3	MY PEL	
		PEL (Total dust)	10 mg/m3	MY PEL	
		TWA (Respirable fraction)	1 mg/m3	ACGIH	
chromium (III) oxide	1308-38-9	TWA	0.5 mg/m3 (chromium)	ACGIH	

Individual protection measures, such as personal protective equipment

Eye/face protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin protection : Choose body protection in relation to its type, to the

Sikafloor®-3 QuartzTop Dark Green



concentration and amount of dangerous substances, and to

the specific work-place.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is

necessary.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the

maximum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

Appearance : powder

Colour : green

Odour : odourless

Odour Threshold : No data available

pH : No data available

Melting point/range / Freezing

point

: No data available

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Sikafloor®-3 QuartzTop Dark Green

Version 2.1 SDS Number: 000000606625 Revision Date: 05.01.2018

Density : No data available

Bulk density : 1,100 kg/m3

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : > 350 °C (> 662 °F)

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : Not applicable

Explosive properties : No data available

Molecular weight : No data available

SECTION 10: Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous

reactions

: Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

Information on likely routes of : None known.

exposure

Acute toxicity

Not classified based on available information.

Components:

chromium (III) oxide:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Sikafloor®-3 QuartzTop Dark Green



Version 2.1 SDS Number: 000000606625

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological

information

: There is no data available for this product.

SECTION 13: Disposal information

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Sikafloor®-3 QuartzTop Dark Green



Revision Date: 05.01.2018

Version 2.1 SDS Number: 000000606625

SECTION 14: Transport information

International Regulations

UNRTDG

Not dangerous goods

IATA-DGR

Not dangerous goods

IMDG-Code

Not dangerous goods

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

SECTION 16: Other information

Date format : dd.mm.yyyy

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!