# Sika® Fastplug 102

SDS Number: 000000606233 Version 2.3 Revision Date: 08.01.2018

# SECTION 1: Identification of the hazardous chemical and of the supplier

Product name : Sika® Fastplug 102

Product code 000000606233

Type of product : solid

### Manufacturer or supplier's details

Company : Sika Kimia Sdn. Bhd.

Lot 689 Nilai Industrial Estate

71800 Nilai

: +60 6799 1762 Telephone

Telefax : +60 6799 1980

E-mail address : EHS@my.sika.com

Emergency telephone

number

Contact point

### **SECTION 2: Hazards identification**

## Classification of the hazardous chemical

Skin corrosion/irritation : Category 2

Serious eye damage/eye

irritation

: Category 1

single exposure

Specific target organ toxicity - : Category 3 (Respiratory system)

# Label elements

Hazard pictograms





Signal word : Danger

Hazard statements : H315 Causes skin irritation.

> H318 Causes serious eye damage. H335 May cause respiratory irritation.

Prevention: Precautionary statements

> P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P280 Wear protective gloves/ eye protection/ face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove victim to fresh air

# Sika® Fastplug 102



and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed. **Disposal:** 

P501 Dispose of contents/ container to an approved waste

disposal plant.

#### Other hazards which do not result in classification

None known.

### SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture

## **Hazardous components**

Chemical name	CAS-No.	Concentration (%)
Cement (chromium reduced)	65997-15-1	>= 30 - < 60
Limestone	1317-65-3	>= 5 - < 10
calcium dihydroxide	1305-62-0	>= 1 - < 3
Quartz (SiO2)	14808-60-7	>= 1 - < 3

#### **SECTION 4: First aid measures**

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

# Sika® Fastplug 102

SDS Number: 000000606233 Version 2.3 Revision Date: 08.01.2018

Most important symptoms and effects, both acute and

delayed

: irritant effects

Cough

Respiratory disorder **Excessive lachrymation** 

**Dermatitis** 

See Section 11 for more detailed information on health effects

and symptoms. Causes skin irritation.

Causes serious eye damage. May cause respiratory irritation.

Notes to physician : Treat symptomatically.

# **SECTION 5: Firefighting measures**

**Extinguishing media** 

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Physicochemical hazards arising from the chemical

Hazardous combustion

products

: No hazardous combustion products are known

Special protective equipment and precautions for fire-fighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing

methods

: Standard procedure for chemical fires.

### **SECTION 6: Accidental release measures**

Personal precautions, protective equipment and emergency procedures

: Use personal protective equipment. Deny access to unprotected persons.

Environmental precautions : Try to prevent the material from entering drains or water

courses.

Methods and materials for containment and cleaning up : Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

# **SECTION 7: Handling and storage**

## Handling

### Precautions for safe handling

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

# Sika® Fastplug 102



Advice on safe handling : Do not breathe vapours/dust.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Follow standard hygiene measures when handling chemical

products

### **Storage**

# Conditions for safe storage, including any incompatibilities

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

### **SECTION 8: Exposure controls and personal protection**

## **Control parameters**

Components  Cement (chromium reduced)	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis MY PEL	
Cernent (chromium reduced)			10 mg/m3		
	Further information: The value is for particulate matter containing no asbestos and <1% crystalline silica  PEL 5 mg/m3 MY PEL				
		(Respirable dust)	3 mg/m3	I WITTEE	
		PEL (Total dust)	10 mg/m3	MY PEL	
		TWA (Respirable fraction)	1 mg/m3	ACGIH	
Limestone	1317-65-3	PEL (Respirable dust)	5 mg/m3	MY PEL	
		PEL (Total dust)	10 mg/m3	MY PEL	
		TWA (particulate)	10 mg/m3 (Calcium carbonate)	MY PEL	
	Further information: The value is for particulate matter containing no asbestos and <1% crystalline silica				
calcium dihydroxide	1305-62-0	TWA	5 mg/m3	MY PEL	
		TWA	5 mg/m3	ACGIH	
Quartz (SiO2)	14808-60-7	TWA (Respirable fraction)	0.1 mg/m3	MY PEL	
		PEL	0.1 mg/m3	MY PEL	

# Sika® Fastplug 102

SDS Number: 000000606233 Version 2.3 Revision Date: 08.01.2018

(Respirable dust)		
TWA (Respirable fraction)	0.025 mg/m3 (Silica)	ACGIH

Individual protection measures, such as personal protective equipment

Eye/face protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is

necessary.

: Use respiratory protection unless adequate local exhaust Respiratory protection

> ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the

maximum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

### **SECTION 9: Physical and chemical properties**

**Appearance** : solid

Colour grey

Odour : odourless

Odour Threshold : No data available

: No data available Hq

Melting point/range / Freezing : No data available

point

Boiling point/boiling range : No data available

Flash point Not applicable

Evaporation rate : No data available

# Sika® Fastplug 102

Version 2.3 SDS Number: 000000606233 Revision Date: 08.01.2018

Flammability : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Density : 1 g/cm3 (20 °C (68 °F) ())

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : Not applicable

Explosive properties : No data available

Molecular weight : No data available

# **SECTION 10: Stability and reactivity**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous

reactions

: Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

No decomposition if stored and applied as directed.

# **SECTION 11: Toxicological information**

Information on likely routes of : None known.

exposure

# Sika® Fastplug 102

Version 2.3 SDS Number: 000000606233 Revision Date: 08.01.2018

#### **Acute toxicity**

No data available

#### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/eye irritation

Causes serious eye damage.

### Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

## Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

### STOT - single exposure

May cause respiratory irritation.

### STOT - repeated exposure

Not classified based on available information.

# **Aspiration toxicity**

Not classified based on available information.

### **SECTION 12: Ecological information**

#### **Ecotoxicity**

No data available

### Persistence and degradability

No data available

## **Bioaccumulative potential**

No data available

### Mobility in soil

No data available

### Other adverse effects

### **Product:**

Additional ecological

information

: There is no data available for this product.

# **SECTION 13: Disposal information**

### **Disposal methods**

Waste from residues : Do not contaminate ponds, waterways or ditches with

chemical or used container.

# Sika® Fastplug 102

Version 2.3 SDS Number: 000000606233 Revision Date: 08.01.2018

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

# **SECTION 14: Transport information**

### International Regulations

**UNRTDG** 

Not dangerous goods

**IATA-DGR** 

Not dangerous goods

**IMDG-Code** 

Not dangerous goods

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### **SECTION 15: Regulatory information**

### Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

#### **SECTION 16: Other information**

Date format : dd.mm.yyyy

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!