

SAFETY DATA SHEET

Sikadur 20 Crack Seal Comp. A



Version 1.0

SDS Number: 000000123447

Revision Date: 06.03.2019

SECTION 1: Identification of the hazardous chemical and of the supplier

Product name : Sikadur 20 Crack Seal Comp. A
Product code : 000000123447
Type of product : liquid

Recommended use of the chemical and restrictions on use

Product use : Special system

Manufacturer or supplier's details


Company : Sika Kimia Sdn. Bhd.
Lot 689 Nilai Industrial Estate
71800 Nilai
Telephone : +60 6799 1762
Telefax : +60 6799 1980
E-mail address : EHS@my.sika.com
Emergency telephone number : -
Contact point :

SECTION 2: Hazards identification

Classification of the hazardous chemical

Skin corrosion/irritation : Category 2
Serious eye damage/eye irritation : Category 2
Skin sensitisation : Category 1
Hazardous to the aquatic environment - chronic hazard : Category 2

Label elements

Hazard pictograms : 

Signal word : Warning

Hazard statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

SAFETY DATA SHEET

Sikadur 20 Crack Seal Comp. A



Version 1.0

SDS Number: 000000123447

Revision Date: 06.03.2019

P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.

Other hazards which do not result in classification

None known.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (%)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)	25068-38-6	\geq 60 - \leq 100
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	\geq 5 - $<$ 10
(1-methylethyl)-1,1'-biphenyl	25640-78-2	\geq 5 - $<$ 10

SECTION 4: First aid measures

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.
Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.

Most important symptoms and effects, both acute and delayed : irritant effects
sensitising effects
Allergic reactions
Excessive lachrymation
Dermatitis
See Section 11 for more detailed information on health effects

SAFETY DATA SHEET

Sikadur 20 Crack Seal Comp. A



Version 1.0

SDS Number: 000000123447

Revision Date: 06.03.2019

and symptoms.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.

Notes to physician : Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Physicochemical hazards arising from the chemical

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

Special protective equipment and precautions for fire-fighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage

Handling

Precautions for safe handling

Advice on protection against : Normal measures for preventive fire protection.



fire and explosion

Advice on safe handling : Do not breathe vapours or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products

Storage

Conditions for safe storage, including any incompatibilities

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Store in accordance with local regulations.

SECTION 8: Exposure controls and personal protection

Control parameters

Contains no substances with occupational exposure limit values.

Individual protection measures, such as personal protective equipment

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

Skin protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.

SAFETY DATA SHEET

Sikadur 20 Crack Seal Comp. A



Version 1.0

SDS Number: 000000123447

Revision Date: 06.03.2019

When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

Appearance	: liquid
Colour	: yellow
Odour	: characteristic
Odour Threshold	: No data available
pH	: ca. 5.2
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: > 101 °C (> 214 °F) Method: closed cup
Evaporation rate	: No data available
Flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: 0.01 hPa (0.01 mmHg)
Relative vapour density	: No data available
Density	: ca. 1.12 g/cm ³ (20 °C (68 °F) ())
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: ca. 1,600 mPa.s (20 °C)

SAFETY DATA SHEET

Sikadur 20 Crack Seal Comp. A



Version 1.0

SDS Number: 000000123447

Revision Date: 06.03.2019

Viscosity, kinematic	: > 7 mm ² /s (40 °C)
Explosive properties	: No data available
Molecular weight	: No data available

SECTION 10: Stability and reactivity

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions.
Conditions to avoid	: No data available
Incompatible materials	: No data available
No decomposition if stored and applied as directed.	

SECTION 11: Toxicological information

Information on likely routes of exposure : None known.

Acute toxicity

Not classified based on available information.

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

SAFETY DATA SHEET

Sikadur 20 Crack Seal Comp. A



Version 1.0

SDS Number: 000000123447

Revision Date: 06.03.2019

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

Ecotoxicity

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l
aquatic invertebrates Exposure time: 48 h

(1-methylethyl)-1,1'-biphenyl:

Toxicity to daphnia and other : LC50 (Daphnia magna (Water flea)): 0.167 mg/l
aquatic invertebrates Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological : An environmental hazard cannot be excluded in the event of
information unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal information

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water
courses or the soil.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.



SECTION 14: Transport information

International Regulations

UNRTDG

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(epoxy resin)
Class : 9
Packing group : III
Labels : 9

IATA-DGR

UN/ID No. : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(epoxy resin)
Class : 9
Packing group : III
Labels : Miscellaneous Dangerous Goods
Packing instruction (cargo aircraft) : 964
Packing instruction (passenger aircraft) : 964

IATA-DGR

Transport in accordance with special regulation A 197

IMDG-Code

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(epoxy resin)
Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

IMDG-Code

Transport in accordance with 2.10.2.7 of the IMDG-Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SAFETY DATA SHEET

Sikadur 20 Crack Seal Comp. A



Version 1.0

SDS Number: 000000123447

Revision Date: 06.03.2019

SECTION 15: Regulatory information

Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

SECTION 16: Other information

Date format : dd.mm.yyyy

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !